



SAFETY DATA SHEET
EcoMotive Trading Ltd - CleanDrive Fuel System Cleaner

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name EcoMotive Trading Ltd - CleanDrive Fuel System Cleaner

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Cleaner

1.3. Details of the supplier of the safety data sheet

Supplier EcoMotive Trading Ltd
 Unit 53d Faircharm Trading
 Estate, Evelyn Drive, Leicester
 Tel: 0845 0521349
 info@eco-motive.com

1.4. Emergency telephone number

Emergency telephone + 0845 0521349 (MON TO FRI 09:00 - 17:00)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

Physical hazards Flam. Liq. 2 - H225

Health hazards Acute Tox. 4 - H332 Skin Irrit. 2 - H315 Eye Dam. 1 - H318 Carc. 2 - H351 STOT SE 3 - H335, H336 STOT RE 2 - H373 Asp. Tox. 1 - H304

Environmental hazards Aquatic Chronic 3 - H412

Human health Vapours and spray/mists in high concentrations are narcotic. See Section 11 for additional information on health hazards.

Environmental The product contains a substance which is harmful to aquatic organisms.

Physicochemical The product is highly flammable. Containers can burst violently or explode when heated, due to excessive pressure build-up. Vapours may form explosive mixtures with air.

2.2. Label elements

Hazard pictograms



Signal word

Danger

EcoMotive Trading Ltd - CleanDrive Fuel System Cleaner

Hazard statements	<p>H225 Highly flammable liquid and vapour. H332 Harmful if inhaled. H315 Causes skin irritation. H318 Causes serious eye damage. H351 Suspected of causing cancer. H335 May cause respiratory irritation. H336 May cause drowsiness or dizziness. H373 May cause damage to organs through prolonged or repeated exposure. H412 Harmful to aquatic life with long lasting effects. H304 May be fatal if swallowed and enters airways.</p>
Precautionary statements	<p>P102 Keep out of reach of children. P202 Do not handle until all safety precautions have been read and understood. P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P243 Take action to prevent static discharges. P260 Do not breathe vapour/ spray. P271 Use only outdoors or in a well-ventilated area. P280 Wear protective gloves/ protective clothing/ eye protection/ face protection. P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor. P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower. P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P312 Call a POISON CENTRE/doctor if you feel unwell. P331 Do NOT induce vomiting. P403+P235 Store in a well-ventilated place. Keep cool. P501 Dispose of contents/ container in accordance with national regulations.</p>
Supplemental label information	<p>EUH066 Repeated exposure may cause skin dryness or cracking. RCH002b For professional users only.</p>
Contains	<p>XYLENE, ACETONE, FUELS DIESEL, BUTAN-1-OL</p>
Supplementary precautionary statements	<p>P201 Obtain special instructions before use. P240 Ground and bond container and receiving equipment. P241 Use explosion-proof electrical equipment. P242 Use non-sparking tools. P261 Avoid breathing vapour/ spray. P264 Wash contaminated skin thoroughly after handling. P273 Avoid release to the environment. P302+P352 IF ON SKIN: Wash with plenty of water. P308+P313 IF exposed or concerned: Get medical advice/ attention. P314 Get medical advice/ attention if you feel unwell. P321 Specific treatment (see medical advice on this label). P332+P313 If skin irritation occurs: Get medical advice/ attention. P362+P364 Take off contaminated clothing and wash it before reuse. P370+P378 In case of fire: Use foam, carbon dioxide, dry powder or water fog to extinguish. P403+P233 Store in a well-ventilated place. Keep container tightly closed. P405 Store locked up.</p>

2.3. Other hazards

This product does not contain any substances classified as PBT or vPvB.

SECTION 3: Composition/information on ingredients

EcoMotive Trading Ltd - CleanDrive Fuel System Cleaner

3.2. Mixtures

XYLENE		30-60%
CAS number: 1330-20-7	EC number: 215-535-7	REACH registration number: 01-2119488216-32-XXXX

Classification

Flam. Liq. 3 - H226
 Acute Tox. 4 - H312
 Acute Tox. 4 - H332
 Skin Irrit. 2 - H315
 Eye Irrit. 2 - H319
 STOT SE 3 - H335
 STOT RE 2 - H373
 Asp. Tox. 1 - H304
 Aquatic Chronic 3 - H412

ACETONE		10-30%
CAS number: 67-64-1	EC number: 200-662-2	REACH registration number: 01-2119471330-49-XXXX

Classification

Flam. Liq. 2 - H225
 Eye Irrit. 2 - H319
 STOT SE 3 - H336

FUELS DIESEL		10-30%
CAS number: 68334-30-5	EC number: 269-822-7	

Classification

Flam. Liq. 3 - H226
 Acute Tox. 4 - H332
 Skin Irrit. 2 - H315
 Carc. 2 - H351
 STOT RE 2 - H373
 Asp. Tox. 1 - H304
 Aquatic Chronic 2 - H411

BUTAN-1-OL		5-10%
CAS number: 71-36-3	EC number: 200-751-6	REACH registration number: 01-2119484630-38-XXXX

Classification

Flam. Liq. 3 - H226
 Acute Tox. 4 - H302
 Skin Irrit. 2 - H315
 Eye Dam. 1 - H318
 STOT SE 3 - H335, H336

EcoMotive Trading Ltd - CleanDrive Fuel System Cleaner

ETHANOL		1-5%
CAS number: 64-17-5	EC number: 200-578-6	REACH registration number: 01-2119457610-43-XXXX
Classification		
Flam. Liq. 2 - H225 Eye Irrit. 2 - H319		
ethyl acetate		<1%
CAS number: 141-78-6	EC number: 205-500-4	REACH registration number: 01-2119475103-46-XXXX
Classification		
Flam. Liq. 2 - H225 Eye Irrit. 2 - H319 STOT SE 3 - H336		
PROPAN-2-OL		<1%
CAS number: 67-63-0	EC number: 200-661-7	REACH registration number: 01-2119457558-25-XXXX
Classification		
Flam. Liq. 2 - H225 Eye Irrit. 2 - H319 STOT SE 3 - H336		

The full text for all hazard statements is displayed in Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information	Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Get medical attention if any discomfort continues.
Inhalation	Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. If in doubt, get medical attention promptly.
Ingestion	Rinse mouth thoroughly with water. Remove person to fresh air and keep comfortable for breathing. Get medical attention.
Skin contact	Wash skin thoroughly with soap and water. Get medical attention promptly if symptoms occur after washing.
Eye contact	Remove any contact lenses and open eyelids wide apart. Rinse immediately with plenty of water. Continue to rinse for at least 15 minutes. Get medical attention promptly if symptoms occur after washing.
Protection of first aiders	First aid personnel should wear appropriate protective equipment during any rescue.

4.2. Most important symptoms and effects, both acute and delayed

General information	See Section 11 for additional information on health hazards.
----------------------------	--

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor	Treat symptomatically.
-----------------------------	------------------------

EcoMotive Trading Ltd - CleanDrive Fuel System Cleaner

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media Foam, carbon dioxide or dry powder.

5.2. Special hazards arising from the substance or mixture

Specific hazards Containers can burst violently or explode when heated, due to excessive pressure build-up.

5.3. Advice for firefighters

Protective actions during firefighting Use water to keep fire exposed containers cool and disperse vapours. Cool containers exposed to heat with water spray and remove them from the fire area if it can be done without risk.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Avoid inhalation of vapours and contact with skin and eyes. Ensure suitable respiratory protection is worn during removal of spillages in confined areas.

6.2. Environmental precautions

Environmental precautions Avoid discharge into drains.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up Eliminate all sources of ignition. No smoking, sparks, flames or other sources of ignition near spillage. Provide adequate ventilation. Absorb in vermiculite, dry sand or earth and place into containers.

6.4. Reference to other sections

Reference to other sections For personal protection, see Section 8. See Section 11 for additional information on health hazards. See Section 12 for additional information on ecological hazards. For waste disposal, see Section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions Keep away from heat, sparks and open flame. Read and follow manufacturer's recommendations. Use suitable respiratory protection if ventilation is inadequate.

Advice on general occupational hygiene Wash promptly with soap and water if skin becomes contaminated. Do not eat, drink or smoke when using this product.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions Protect from freezing and direct sunlight. Store in a dry place. Do not store near heat sources or expose to high temperatures. Keep away from heat, sparks and open flame.

7.3. Specific end use(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.2.

SECTION 8: Exposure controls/Personal protection

8.1. Control parameters

Occupational exposure limits

XYLENE

EcoMotive Trading Ltd - CleanDrive Fuel System Cleaner

Long-term exposure limit (8-hour TWA): WEL 50 ppm 220 mg/m³

Long-term exposure limit (8-hour TWA): WEL 50 ppm 220 mg/m³

Short-term exposure limit (15-minute): WEL 100 ppm 441 mg/m³

Short-term exposure limit (15-minute): WEL 100 ppm 441 mg/m³

Sk, Sk

ACETONE

Long-term exposure limit (8-hour TWA): WEL 500 ppm 1210 mg/m³

Long-term exposure limit (8-hour TWA): WEL 500 ppm 1210 mg/m³

Short-term exposure limit (15-minute): WEL 1500 ppm 3620 mg/m³

Short-term exposure limit (15-minute): WEL 1500 ppm 3620 mg/m³

BUTAN-1-OL

Short-term exposure limit (15-minute): WEL 154 mg/m³ 50 ppm

ETHANOL

Long-term exposure limit (8-hour TWA): WEL 1000 ppm 1920 mg/m³

Long-term exposure limit (8-hour TWA): WEL 1000 ppm 1920 mg/m³

ethyl acetate

Long-term exposure limit (8-hour TWA): WEL 200 ppm

Short-term exposure limit (15-minute): WEL 400 ppm

PROPAN-2-OL

Long-term exposure limit (8-hour TWA): WEL 400 ppm 999 mg/m³

Long-term exposure limit (8-hour TWA): WEL 400 ppm 999 mg/m³

Long-term exposure limit (8-hour TWA): WEL 400 ppm 999 mg/m³

Short-term exposure limit (15-minute): WEL 500 ppm 1250 mg/m³

Short-term exposure limit (15-minute): WEL 500 ppm 1250 mg/m³

Short-term exposure limit (15-minute): WEL 500 ppm 1250 mg/m³

WEL = Workplace Exposure Limit

Sk = Can be absorbed through the skin.

XYLENE (CAS: 1330-20-7)

DNEL

Consumer - Dermal; Long term systemic effects: 108 mg/kg/day

Workers - Dermal; Long term systemic effects: 180 mg/kg/day

Consumer - Inhalation; Short term local effects: 174 mg/m³

Consumer - Inhalation; Short term systemic effects: 174 mg/m³

Workers - Inhalation; Short term systemic effects: 289 mg/m³

Workers - Inhalation; Short term local effects: 289 mg/m³

Consumer - Inhalation; Long term systemic effects: 14.8 mg/m³

Workers - Inhalation; Long term systemic effects: 77 mg/m³

PNEC

- Fresh water; 0.327 mg/l

- marine water; 0.327 mg/l

- Intermittent release; 0.327 mg/l

- STP; 6.58 mg/l

- Sediment (Freshwater); 12.46 mg/kg

- Sediment (Marinewater); 12.46 mg/kg

- Soil; 2.31 mg/kg

ACETONE (CAS: 67-64-1)

DNEL

Workers - Dermal; Long term systemic effects: 186 mg/kg/day

Workers - Inhalation; Short term local effects: 2420 mg/m³

Workers - Inhalation; Long term systemic effects: 1210 mg/m³

EcoMotive Trading Ltd - CleanDrive Fuel System Cleaner

- PNEC**
- Sediment (Freshwater); 30.4 mg/kg
 - Sediment (Marinewater); 3.04 mg/kg
 - marine water; 1.06 mg/l
 - Soil; 29.5 mg/kg

BUTAN-1-OL (CAS: 71-36-3)

- DNEL**
- Consumer - Oral; Long term systemic effects: 3.125 mg/kg/day
 Consumer - Inhalation; Long term local effects: 55 mg/m³
 Workers - Inhalation; Long term local effects: 310 mg/m³

- PNEC**
- Fresh water; 0.082 mg/l
 - Sediment (Freshwater); 0.178 mg/kg
 - Intermittent release; 2.25 mg/l
 - Sediment (Marinewater); 0.0178 mg/kg
 - marine water; 0.0082 mg/l
 - STP; 2476 mg/l
 - Soil; 0.015 mg/kg

ETHANOL (CAS: 64-17-5)

- DNEL**
- Consumer - Oral; Long term systemic effects: 87 mg/kg/day
 Consumer - Dermal; Long term systemic effects: 206 mg/kg/day
 Workers - Dermal; Long term systemic effects: 343 mg/kg/day
 Consumer - Inhalation; Short term local effects: 950 mg/m³
 Workers - Inhalation; Short term local effects: 1900 mg/m³
 Consumer - Inhalation; Long term systemic effects: 114 mg/m³
 Workers - Inhalation; Long term systemic effects: 950 mg/m³

- PNEC**
- Fresh water; 0.96 mg/l
 - Sediment (Freshwater); 3.6 mg/kg
 - marine water; 0.79 mg/l
 - Soil; 0.63 mg/kg

PROPAN-2-OL (CAS: 67-63-0)

- DNEL**
- Workers - Dermal; Long term systemic effects: 888 mg/kg/day
 Workers - Inhalation; Long term systemic effects: 500 mg/m³
 Consumer - Dermal; Long term systemic effects: 319 mg/kg/day
 Consumer - Inhalation; Long term systemic effects: 89 mg/m³
 Consumer - Oral; Long term systemic effects: 26 mg/kg/day

- PNEC**
- Fresh water; 140.9 mg/l
 - marine water; 140.9 mg/l
 - Intermittent release; 140.9 mg/l
 - STP; 2251 mg/l
 - Soil; 28 mg/kg
 - Sediment; 552 mg/kg

8.2. Exposure controls

Eye/face protection

Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible.

Hand protection

The most suitable glove should be chosen in consultation with the glove supplier/manufacturer, who can provide information about the breakthrough time of the glove material.

EcoMotive Trading Ltd - CleanDrive Fuel System Cleaner

Other skin and body protection	Wear suitable protective equipment for prolonged exposure and/or high concentrations of vapours, spray or mist.
Respiratory protection	No specific recommendations. If ventilation is inadequate, suitable respiratory protection must be worn.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance	Liquid.
Colour	Clear.
Odour	Solvent.
Odour threshold	No information available.
pH	No information available.
Melting point	No information available.
Initial boiling point and range	76 (76 TO 138)°C @
Flash point	-18°C Closed cup.
Evaporation rate	No information available.
Evaporation factor	No information available.
Flammability (solid, gas)	No information available.
Upper/lower flammability or explosive limits	Lower flammable/explosive limit: 0.8 % Upper flammable/explosive limit: 15.0 %
Vapour pressure	No information available.
Vapour density	No information available.
Relative density	No information available.
Solubility(ies)	Slightly soluble in water.
Partition coefficient	No information available.
Auto-ignition temperature	355°C
Decomposition Temperature	No information available.
Viscosity	No information available.
Explosive properties	No information available.
Oxidising properties	No information available.

9.2. Other information

Other information	None.
--------------------------	-------

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity	No test data specifically related to reactivity available for this product or its ingredients.
-------------------	--

10.2. Chemical stability

Stability	The product may not be stable under some conditions of storage or use.
------------------	--

10.3. Possibility of hazardous reactions

EcoMotive Trading Ltd - CleanDrive Fuel System Cleaner

Possibility of hazardous reactions None known.

10.4. Conditions to avoid

Conditions to avoid Avoid heat, flames and other sources of ignition. Avoid exposure to high temperatures or direct sunlight.

10.5. Incompatible materials

Materials to avoid None known.

10.6. Hazardous decomposition products

Hazardous decomposition products None at ambient temperatures.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity - oral

ATE oral (mg/kg) 10,000.0

Acute toxicity - dermal

ATE dermal (mg/kg) 2,200.0

Acute toxicity - inhalation

ATE inhalation (vapours mg/l) 16.92

Inhalation	Harmful if inhaled. May cause respiratory irritation. May cause drowsiness or dizziness. Vapours in high concentrations are narcotic. Vapours may cause headache, fatigue, dizziness and nausea.
Ingestion	May be fatal if swallowed and enters airways.
Skin contact	Causes skin irritation.
Eye contact	Causes serious eye damage.
Acute and chronic health hazards	May cause damage to organs through prolonged or repeated exposure. Suspected of causing cancer.
Route of exposure	Inhalation Ingestion Skin and/or eye contact

Toxicological information on ingredients.

XYLENE

Acute toxicity - oral

Acute toxicity oral (LD₅₀ mg/kg) 4,300.0

Species Rat

ATE oral (mg/kg) 4,300.0

Acute toxicity - dermal

Acute toxicity dermal (LD₅₀ mg/kg) 3,200.0

Species Rabbit

EcoMotive Trading Ltd - CleanDrive Fuel System Cleaner

ATE dermal (mg/kg) 1,100.0

Acute toxicity - inhalation

ATE inhalation (vapours mg/l) 11.0

ACETONE

Acute toxicity - oral

Acute toxicity oral (LD₅₀ mg/kg) 5,800.0

Species Rat

ATE oral (mg/kg) 5,800.0

Acute toxicity - dermal

Acute toxicity dermal (LD₅₀ mg/kg) 7,800.0

Species Rabbit

ATE dermal (mg/kg) 7,800.0

Acute toxicity - inhalation

Acute toxicity inhalation (LC₅₀ vapours mg/l) 21.0

Species Rat

ATE inhalation (vapours mg/l) 21.0

FUELS DIESEL

Acute toxicity - inhalation

ATE inhalation (vapours mg/l) 11.0

BUTAN-1-OL

Acute toxicity - oral

Acute toxicity oral (LD₅₀ mg/kg) 2,001.0

Species Rat

ATE oral (mg/kg) 500.0

Acute toxicity - dermal

Acute toxicity dermal (LD₅₀ mg/kg) 3,430.0

Species Rabbit

ATE dermal (mg/kg) 3,430.0

Acute toxicity - inhalation

EcoMotive Trading Ltd - CleanDrive Fuel System Cleaner

Acute toxicity inhalation (LC₅₀ vapours mg/l) 20.1

Species Rat

ATE inhalation (vapours mg/l) 20.1

ETHANOL

Acute toxicity - oral

Acute toxicity oral (LD₅₀ mg/kg) 7,060.0

Species Rat

ATE oral (mg/kg) 7,060.0

Acute toxicity - dermal

Acute toxicity dermal (LD₅₀ mg/kg) 2,001.0

Species Rabbit

ATE dermal (mg/kg) 2,001.0

Acute toxicity - inhalation

Acute toxicity inhalation (LC₅₀ vapours mg/l) 20,000.0

Species Rat

ATE inhalation (vapours mg/l) 20,000.0

PROPAN-2-OL

Acute toxicity - oral

Acute toxicity oral (LD₅₀ mg/kg) 5,045.0

Species Rat

ATE oral (mg/kg) 5,045.0

Acute toxicity - dermal

Acute toxicity dermal (LD₅₀ mg/kg) 12,800.0

Species Rabbit

ATE dermal (mg/kg) 12,800.0

Acute toxicity - inhalation

Acute toxicity inhalation (LC₅₀ vapours mg/l) 30.0

Species Rat

EcoMotive Trading Ltd - CleanDrive Fuel System Cleaner

ATE inhalation (vapours
mg/l) 30.0

SECTION 12: Ecological information

12.1. Toxicity

Ecological information on ingredients.

XYLENE

Acute aquatic toxicity

Acute toxicity - fish LOEC, : >1 - <10 mg/l, Fish

Acute toxicity - aquatic plants LOEC, : >1 - <10 mg/l, Algae

ACETONE

Acute aquatic toxicity

Acute toxicity - fish EC₅₀, 96 hours: 8300 mg/l, Lepomis macrochirus (Bluegill)

Acute toxicity - aquatic invertebrates EC₅₀, : 8800 mg/l, Daphnia magna

BUTAN-1-OL

Acute aquatic toxicity

Acute toxicity - fish LC₅₀, 96 hours: 1376 mg/l, Pimephales promelas (Fat-head Minnow)

Acute toxicity - aquatic invertebrates LC₅₀, 96 hours: 1328 mg/l, Daphnia magna

Acute toxicity - aquatic plants EC₅₀, 96 hours: 225 mg/l, Selenastrum capricornutum

ETHANOL

Acute aquatic toxicity

Acute toxicity - fish LC₅₀, 96 hours: 1030 mg/l, Fish

Acute toxicity - aquatic invertebrates EC₅₀, 24 hours: 101 mg/l, Daphnia magna

PROPAN-2-OL

Acute aquatic toxicity

Acute toxicity - fish LC₅₀, 96 hours: 9640 mg/l, Pimephales promelas (Fat-head Minnow)

Acute toxicity - aquatic invertebrates EC₅₀, 48 hours: 13299 mg/l, Daphnia magna

Acute toxicity - aquatic plants EC₅₀, 72 hours: >1 mg/l, Desmodemus subspicatus

12.2. Persistence and degradability

Persistence and degradability No data available.

12.3. Bioaccumulative potential

EcoMotive Trading Ltd - CleanDrive Fuel System Cleaner

Partition coefficient No information available.

12.4. Mobility in soil

Mobility No data available

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB assessment This product does not contain any substances classified as PBT or vPvB.

12.6. Other adverse effects

Other adverse effects None known.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

General information Dispose of waste product or used containers in accordance with local regulations Waste codes should be assigned by the user, preferably in discussion with the waste disposal authorities.

Disposal methods Containers should be thoroughly emptied before disposal because of the risk of an explosion. Do not pierce or burn, even after use.

Waste class The waste code classification is to be carried out according to the European Waste Catalogue (EWC).

SECTION 14: Transport information

14.1. UN number

UN No. (ADR/RID) 1993

UN No. (IMDG) 1993

UN No. (ICAO) 1993

UN No. (ADN) 1993

14.2. UN proper shipping name

Proper shipping name (ADR/RID) FLAMMABLE LIQUID, N.O.S.

Proper shipping name (IMDG) FLAMMABLE LIQUID, N.O.S.

Proper shipping name (ICAO) FLAMMABLE LIQUID, N.O.S.

Proper shipping name (ADN) FLAMMABLE LIQUID, N.O.S.

14.3. Transport hazard class(es)

ADR/RID class 3

ADR/RID classification code F1

ADR/RID label 3

IMDG class 3

ICAO class/division 3

ADN class 3

EcoMotive Trading Ltd - CleanDrive Fuel System Cleaner

Transport labels



14.4. Packing group

ADR/RID packing group	II
IMDG packing group	II
ICAO packing group	II
ADN packing group	II

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant

No.

14.6. Special precautions for user

EmS	F-E, S-E
ADR transport category	2
Emergency Action Code	•3YE
Hazard Identification Number (ADR/RID)	33
Tunnel restriction code	(D/E)

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU legislation	Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as amended). Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (as amended). Directive 2008/98/EC of the European Parliament and of the Council of 19 November 2008 on waste.
----------------	--

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

SECTION 16: Other information

Revision date	20/05/2019
Revision	1
SDS number	7874

EcoMotive Trading Ltd - CleanDrive Fuel System Cleaner

Hazard statements in full	H225 Highly flammable liquid and vapour. H226 Flammable liquid and vapour. H302 Harmful if swallowed. H304 May be fatal if swallowed and enters airways. H312 Harmful in contact with skin. H315 Causes skin irritation. H318 Causes serious eye damage. H319 Causes serious eye irritation. H332 Harmful if inhaled. H335 May cause respiratory irritation. H336 May cause drowsiness or dizziness. H351 Suspected of causing cancer. H373 May cause damage to organs through prolonged or repeated exposure. H411 Toxic to aquatic life with long lasting effects. H412 Harmful to aquatic life with long lasting effects.
----------------------------------	--

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.