

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Trade name : QUIXX Paint
UFI : N600-6056-9003-58RE
Type of product : Paint, Varnish

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Intended for general public
Main use category : Consumer use
Use of the substance/mixture : Plating agent
Paints and Varnishes

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Manufacturer/Supplier

E.V.I. GmbH
Hainbuchenring 4
DE- 82061 Neuried
Germany
T +49 (0)89 745062-0 - F +49 (0)89 745062-99
www.e-v-i.de

Email competent person

sds@kft.de

Importer

JRP Distribution Ltd
Unit 10A, Chichester Business Park, City Fields Way Tangmere, West
Sussex, PO20 2FT
T +44 1903 750355
sales@jrpdistribution.co.uk

1.4. Emergency telephone number

Country	Organisation/Company	Address	Emergency number	Comment
United Kingdom	National Health Service (NHS) England / Scotland / Wales / Northern Ireland	-	England / Scotland: 111 Wales: 111 or 0845 46 47 Northern Ireland: call your local General Practitioner. For life-threatening emergencies: call 999 for an ambulance.	24 h medical helpline for general public

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Flammable liquids, Category 3 H226
Specific target organ toxicity – Single exposure, Category 3, Narcosis H336
Full text of H- and EUH-statements: see section 16

Adverse physicochemical, human health and environmental effects

Flammable liquid and vapour. May cause drowsiness or dizziness.

QUIXX Paint


Safety Data Sheet

According to REACH Regulation (EC) No 1907/2006, as retained and amended in UK law

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)



Signal word (CLP)

Contains

Hazard statements (CLP)

Precautionary statements (CLP)

EUH-statements

Extra phrases

Child-resistant fastening

Tactile warning

- : Warning
- : n-butyl acetate; 2-methoxy-1-methylethyl acetate; acetone
- : H226 - Flammable liquid and vapour.
H336 - May cause drowsiness or dizziness.
- : P101 - If medical advice is needed, have product container or label at hand.
P102 - Keep out of reach of children.
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.
No smoking.
P261 - Avoid breathing vapours.
P271 - Use only outdoors or in a well-ventilated area.
P312 - Call a POISON CENTER, doctor if you feel unwell.
P403+P235 - Store in a well-ventilated place. Keep cool.
P405 - Store locked up.
P501 - Dispose of contents, container to a hazardous or special waste collection point.
- : EUH066 - Repeated exposure may cause skin dryness or cracking.
- : INCI Name.
BUTYL ACETATE; METHOXYISOPROPYL ACETATE; ACETONE.
For professional users only.
- : Not applicable
- : Not applicable

2.3. Other hazards

Contains no PBT/vPvB substances $\geq 0.1\%$ assessed in accordance with REACH Annex XIII

Component	
n-butyl acetate (123-86-4)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
xylene (1330-20-7)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
Ethanol (64-17-5)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
2-methoxy-1-methylethyl acetate (108-65-6)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
aluminium powder (stabilised) (7429-90-5)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
bis(2-ethylhexyl) adipate (103-23-1)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
acetone (67-64-1)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
Naphtha (petroleum), hydrotreated heavy (64742-48-9)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
Silicon dioxide (7631-86-9)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter $\leq 10 \mu\text{m}$] (13463-67-7)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII

QUIXX Paint

Safety Data Sheet

According to REACH Regulation (EC) No 1907/2006, as retained and amended in UK law

propan-2-ol (67-63-0)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
Diiron trioxide (1309-37-1)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
29H,31H-phthalocyaninato(2-)-N29,N30,N31,N32 copper (147-14-8)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
Carbon black (1333-86-4)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
n-butyl acetate substance with national workplace exposure limit(s) (GB); substance with a Community workplace exposure limit	CAS-No.: 123-86-4 EC-No.: 204-658-1 EC Index-No.: 607-025-00-1 REACH-no: 01-2119485493-29-xxxx	≥ 25 – < 50	Flam. Liq. 3, H226 STOT SE 3, H336 EUH066
xylene substance with national workplace exposure limit(s) (GB); substance with a Community workplace exposure limit	REACH-no: 01-2119488216-32-xxxx	≥ 5 – < 10	Flam. Liq. 3, H226 Acute Tox. 4 (Dermal), H312 (ATE=1000 mg/kg bodyweight) Acute Tox. 4 (Inhalation:vapour), H332 (ATE=11 mg/l/4h) Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335 STOT RE 2, H373 Asp. Tox. 1, H304
Ethanol substance with national workplace exposure limit(s) (GB)	CAS-No.: 64-17-5 EC-No.: 200-578-6 EC Index-No.: 603-002-00-5 REACH-no: 01-2119457610-43-xxxx	≥ 2.5 – < 5	Flam. Liq. 2, H225 Eye Irrit. 2, H319
2-methoxy-1-methylethyl acetate substance with national workplace exposure limit(s) (GB); substance with a Community workplace exposure limit	CAS-No.: 108-65-6 EC-No.: 203-603-9 EC Index-No.: 607-195-00-7 REACH-no: 01-2119475791-29-xxxx	≥ 2.5 – < 5	Flam. Liq. 3, H226 STOT SE 3, H336
aluminium powder (stabilised) substance with national workplace exposure limit(s) (GB) (Note T)	CAS-No.: 7429-90-5 EC-No.: 231-072-3 EC Index-No.: 013-002-00-1 REACH-no: 01-2119529243-45-xxxx	≥ 2.5 – < 5	Flam. Sol. 1, H228

QUIXX Paint

Safety Data Sheet

According to REACH Regulation (EC) No 1907/2006, as retained and amended in UK law

acetone substance with national workplace exposure limit(s) (GB); substance with a Community workplace exposure limit	CAS-No.: 67-64-1 EC-No.: 200-662-2 EC Index-No.: 606-001-00-8 REACH-no: 01-2119471330- 49-xxxx	≥ 1 – < 2.5	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336 EUH066
Naphtha (petroleum), hydrotreated heavy substance with a Community workplace exposure limit (Note P)	CAS-No.: 64742-48-9 EC-No.: 265-150-3 EC Index-No.: 649-327-00-6 REACH-no: 01-2119486659- 16-xxxx	≥ 1 – < 2.5	Asp. Tox. 1, H304
titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm] substance with national workplace exposure limit(s) (GB) (Note V)(Note W)(Note 10)	CAS-No.: 13463-67-7 EC-No.: 236-675-5 EC Index-No.: 022-006-00-2 REACH-no: 01-2119489379- 17-xxxx	< 1	Carc. 2, H351
propan-2-ol substance with national workplace exposure limit(s) (GB)	CAS-No.: 67-63-0 EC-No.: 200-661-7 EC Index-No.: 603-117-00-0	< 1	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336
Diiron trioxide substance with national workplace exposure limit(s) (GB)	CAS-No.: 1309-37-1 EC-No.: 215-168-2	< 1	Not classified
Carbon black substance with national workplace exposure limit(s) (GB)	CAS-No.: 1333-86-4 EC-No.: 215-609-9	< 1	Not classified
naphtha (petroleum), hydrodesulphurized heavy substance with a Community workplace exposure limit (Note P)	CAS-No.: 64742-82-1 EC-No.: 265-185-4 EC Index-No.: 649-330-00-2 REACH-no: 01-2119490979- 12-xxxx	< 1	Flam. Liq. 3, H226 STOT RE 1, H372 Asp. Tox. 1, H304 Aquatic Chronic 1, H410

Specific concentration limits:

Name	Product identifier	Specific concentration limits
xylene	REACH-no: 01-2119488216- 32-xxxx	(10 ≤C < 100) STOT RE 2, H373
Ethanol	CAS-No.: 64-17-5 EC-No.: 200-578-6 EC Index-No.: 603-002-00-5 REACH-no: 01-2119457610- 43-xxxx	(50 ≤C < 100) Eye Irrit. 2, H319

Note 10: The classification as a carcinogen by inhalation applies only to mixtures in powder form containing 1 % or more of titanium dioxide which is in the form of or incorporated in particles with aerodynamic diameter ≤ 10 µm.

Note P: Note P : The classification as a carcinogen or mutagen need not apply if it can be shown that the substance contains less than 0,1 % w/w benzene (EINECS No 200-753-7). When the substance is not classified as a carcinogen at least the precautionary statements (P102-)P260-P262- P301 + P310-P331 (Table 3.1) or the S-phrases (2-)23-24-62 (Table 3.2) shall apply. This note applies only to certain complex oil-derived substances in Part 3.

Note T: This substance may be marketed in a form which does not have the physical hazards as indicated by the classification in the entry in Part 3. If the results of the relevant method or methods in accordance with Part 2 of Annex I of this Regulation show that the specific form of substance marketed does not exhibit this physical property or these physical hazards, the substance shall be classified in accordance with the result or results of this test or these tests. Relevant information, including reference to the relevant test method(s) shall be included in the safety data sheet.

Note V: If the substance is to be placed on the market as fibres (with diameter < 3 µm, length > 5 µm and aspect ratio ≥ 3:1) or particles of the substance fulfilling the WHO fibre criteria or as particles with modified surface chemistry, their hazardous properties must be evaluated in accordance with Title II of this Regulation, to assess whether a higher category (Carc. 1B or 1A) and/or additional routes of exposure (oral or dermal) should be applied.

QUIXX Paint

Safety Data Sheet

According to REACH Regulation (EC) No 1907/2006, as retained and amended in UK law

Note W: It has been observed that the carcinogenic hazard of this substance arises when respirable dust is inhaled in quantities leading to significant impairment of particle clearance mechanisms in the lung. This note aims to describe the particular toxicity of the substance; it does not constitute a criterion for classification according to this Regulation.

Full text of H- and EUH-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general	: In all cases of doubt, or when symptoms persist, seek medical attention.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact	: Rinse skin with water/shower. Take off immediately all contaminated clothing.
First-aid measures after eye contact	: Rinse eyes with water as a precaution.
First-aid measures after ingestion	: Call a poison center or a doctor if you feel unwell.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects	: May cause drowsiness or dizziness.
Symptoms/effects after skin contact	: Repeated exposure may cause skin dryness or cracking.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	: Use extinguishing media appropriate for surrounding fire. Water spray. Dry powder. Foam. Carbon dioxide.
Unsuitable extinguishing media	: Strong water jet.

5.2. Special hazards arising from the substance or mixture

Fire hazard	: Flammable liquid and vapour.
Explosion hazard	: Explosive vapour/air mixtures may be formed.
Hazardous decomposition products in case of fire	: Toxic fumes may be released. Carbon dioxide. Carbon monoxide. Nitrogen oxides.

5.3. Advice for firefighters

Protection during firefighting	: Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.
Other information	: Do not allow run-off from fire fighting to enter drains or water courses. Disposal must be done according to official regulations.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures	: Ventilate spillage area. No open flames, no sparks, and no smoking. Avoid breathing vapours.
----------------------	--

6.1.2. For emergency responders

Protective equipment	: Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".
----------------------	---

6.2. Environmental precautions

Avoid sub-soil penetration. Prevent entry to sewers and public waters. Notify authorities if product enters sewers or public waters.

QUIXX Paint

Safety Data Sheet

According to REACH Regulation (EC) No 1907/2006, as retained and amended in UK law

6.3. Methods and material for containment and cleaning up

- Methods for cleaning up : Cover spill with non combustible material, e.g.: sand, earth, vermiculite. Take up mechanically (sweeping, shovelling) and collect in suitable container for disposal. Notify authorities if product enters sewers or public waters.
- Other information : Disposal must be done according to official regulations.

6.4. Reference to other sections

Information for safe handling. See section 7. Concerning personal protective equipment to use, see section 8. For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Additional hazards when processed : In use, may form flammable vapour-air mixture.
- Precautions for safe handling : Ensure good ventilation of the work station. Wear personal protective equipment. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Flammable vapours may accumulate in the container. Use explosion-proof equipment. Use only outdoors or in a well-ventilated area. Avoid breathing vapours.
- Hygiene measures : Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

- Technical measures : Ground/bond container and receiving equipment.
- Storage conditions : Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store locked up.
- Heat and ignition sources : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep away from heat and direct sunlight.
- Information about storage in one common storage facility : Keep away from food, drink and animal feeding stuffs.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1 National occupational exposure and biological limit values

n-butyl acetate (123-86-4)	
EU - Indicative Occupational Exposure Limit (IOEL)	
Local name	n-Butyl acetate
IOEL TWA	241 mg/m ³
IOEL TWA [ppm]	50 ppm
IOEL STEL	723 mg/m ³
IOEL STEL [ppm]	150 ppm
Regulatory reference	COMMISSION DIRECTIVE (EU) 2019/1831
United Kingdom - Occupational Exposure Limits	
Local name	Butyl acetate
WEL TWA (OEL TWA) [1]	724 mg/m ³
WEL TWA (OEL TWA) [2]	150 ppm

QUIXX Paint

Safety Data Sheet

According to REACH Regulation (EC) No 1907/2006, as retained and amended in UK law

WEL STEL (OEL STEL)	966 mg/m ³
WEL STEL (OEL STEL) [ppm]	200 ppm
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE
xylene (1330-20-7)	
EU - Indicative Occupational Exposure Limit (IOEL)	
Local name	Xylene, mixed isomers, pure
IOEL TWA	221 mg/m ³
IOEL TWA [ppm]	50 ppm
IOEL STEL	442 mg/m ³
IOEL STEL [ppm]	100 ppm
Remark	Skin
Regulatory reference	COMMISSION DIRECTIVE 2000/39/EC
United Kingdom - Occupational Exposure Limits	
Local name	Xylene
WEL TWA (OEL TWA) [1]	220 mg/m ³ o-,m-,p- or mixed isomers
WEL TWA (OEL TWA) [2]	50 ppm o-,m-,p- or mixed isomers
WEL STEL (OEL STEL)	441 mg/m ³ o-,m-,p- or mixed isomers
WEL STEL (OEL STEL) [ppm]	100 ppm o-,m-,p- or mixed isomers
Remark	Sk (Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity)
Regulatory reference	EH40/2005 (Third edition, 2018). HSE
United Kingdom - Biological limit values	
Local name	Xylene, o-, m-, p- or mixed isomers
BMGV	650 mmol/mol Creatinine Parameter: methyl hippuric acid - Medium: urine - Sampling time: Post shift
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE
Ethanol (64-17-5)	
United Kingdom - Occupational Exposure Limits	
Local name	Ethanol
WEL TWA (OEL TWA) [1]	1920 mg/m ³
WEL TWA (OEL TWA) [2]	1000 ppm
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE
2-methoxy-1-methylethyl acetate (108-65-6)	
EU - Indicative Occupational Exposure Limit (IOEL)	
Local name	2-Methoxy-1-methylethylacetate
IOEL TWA	275 mg/m ³
IOEL TWA [ppm]	50 ppm
IOEL STEL	550 mg/m ³
IOEL STEL [ppm]	100 ppm
Remark	Skin

QUIXX Paint

Safety Data Sheet

According to REACH Regulation (EC) No 1907/2006, as retained and amended in UK law

Regulatory reference	COMMISSION DIRECTIVE 2000/39/EC
United Kingdom - Occupational Exposure Limits	
Local name	1-Methoxypropyl acetate
WEL TWA (OEL TWA) [1]	274 mg/m ³
WEL TWA (OEL TWA) [2]	50 ppm
WEL STEL (OEL STEL)	548 mg/m ³
WEL STEL (OEL STEL) [ppm]	100 ppm
Remark	Sk (Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity)
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE
aluminium powder (stabilised) (7429-90-5)	
United Kingdom - Occupational Exposure Limits	
Local name	Aluminium
WEL TWA (OEL TWA) [1]	2 mg/m ³ alkyl compounds 2 mg/m ³ salts, soluble 10 mg/m ³ metal, inhalable dust 4 mg/m ³ metal, respirable dust
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE
acetone (67-64-1)	
EU - Indicative Occupational Exposure Limit (IOEL)	
Local name	Acetone
IOEL TWA	1210 mg/m ³
IOEL TWA [ppm]	500 ppm
Regulatory reference	COMMISSION DIRECTIVE 2000/39/EC
United Kingdom - Occupational Exposure Limits	
Local name	Acetone
WEL TWA (OEL TWA) [1]	1210 mg/m ³
WEL TWA (OEL TWA) [2]	500 ppm
WEL STEL (OEL STEL)	3620 mg/m ³
WEL STEL (OEL STEL) [ppm]	1500 ppm
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE
Naphtha (petroleum), hydrotreated heavy (64742-48-9)	
EU - Indicative Occupational Exposure Limit (IOEL)	
Local name	White spirit Type 3
IOEL TWA	116 mg/m ³
IOEL TWA [ppm]	20 ppm
IOEL STEL	290 mg/m ³
IOEL STEL [ppm]	50 ppm
Remark	Skin. (Year of adoption 2007)
Regulatory reference	SCOEL Recommendations

QUIXX Paint

Safety Data Sheet

According to REACH Regulation (EC) No 1907/2006, as retained and amended in UK law

titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter $\leq 10 \mu\text{m}$] (13463-67-7)	
United Kingdom - Occupational Exposure Limits	
Local name	Titanium dioxide
WEL TWA (OEL TWA) [1]	4 mg/m ³ respirable 10 mg/m ³ total inhalable
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE
propan-2-ol (67-63-0)	
United Kingdom - Occupational Exposure Limits	
Local name	Propan-2-ol
WEL TWA (OEL TWA) [1]	999 mg/m ³
WEL TWA (OEL TWA) [2]	400 ppm
WEL STEL (OEL STEL)	1250 mg/m ³
WEL STEL (OEL STEL) [ppm]	500 ppm
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE
Diiron trioxide (1309-37-1)	
United Kingdom - Occupational Exposure Limits	
Local name	Iron oxide
WEL TWA (OEL TWA) [1]	5 mg/m ³ fume (as Fe)
WEL STEL (OEL STEL)	10 mg/m ³ fume (as Fe)
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE
Carbon black (1333-86-4)	
United Kingdom - Occupational Exposure Limits	
Local name	Carbon black
WEL TWA (OEL TWA) [1]	3.5 mg/m ³
WEL STEL (OEL STEL)	7 mg/m ³
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE
naphtha (petroleum), hydrodesulphurized heavy (64742-82-1)	
EU - Indicative Occupational Exposure Limit (IOEL)	
Local name	White spirit Type 1
IOEL TWA	116 mg/m ³
IOEL TWA [ppm]	20 ppm
IOEL STEL	290 mg/m ³
IOEL STEL [ppm]	50 ppm
Remark	Skin. (Year of adoption 2007)
Regulatory reference	SCOEL Recommendations

8.1.2. Recommended monitoring procedures

No additional information available

8.1.3. Air contaminants formed

No additional information available

QUIXX Paint

Safety Data Sheet

According to REACH Regulation (EC) No 1907/2006, as retained and amended in UK law

8.1.4. DNEL and PNEC

n-butyl acetate (123-86-4)	
DNEL/DMEL (Workers)	
Acute - systemic effects, dermal	11 mg/kg bodyweight/day
Acute - systemic effects, inhalation	600 mg/m ³
Acute - local effects, inhalation	600 mg/m ³
Long-term - systemic effects, dermal	11 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	300 mg/m ³
Long-term - local effects, inhalation	300 mg/m ³
DNEL/DMEL (General population)	
Acute - systemic effects, dermal	6 mg/kg bodyweight
Acute - systemic effects, inhalation	300 mg/m ³
Acute - systemic effects, oral	2 mg/kg bodyweight
Acute - local effects, inhalation	300 mg/m ³
Long-term - systemic effects, oral	2 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	35.7 mg/m ³
Long-term - systemic effects, dermal	6 mg/kg bodyweight/day
Long-term - local effects, inhalation	35.7 mg/m ³
PNEC (Water)	
PNEC aqua (freshwater)	0.18 mg/l
PNEC aqua (marine water)	0.018 mg/l
PNEC aqua (intermittent, freshwater)	0.36 mg/l
PNEC (Sediment)	
PNEC sediment (freshwater)	0.981 mg/kg dwt
PNEC sediment (marine water)	0.0981 mg/kg dwt
PNEC (Soil)	
PNEC soil	0.0903 mg/kg dwt
PNEC (STP)	
PNEC sewage treatment plant	35.6 mg/l
xylene	
DNEL/DMEL (Workers)	
Acute - systemic effects, inhalation	442 mg/m ³
Acute - local effects, inhalation	442 mg/m ³
Long-term - systemic effects, dermal	212 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	221 mg/m ³
Long-term - local effects, inhalation	221 mg/m ³
DNEL/DMEL (General population)	
Acute - systemic effects, inhalation	260 mg/m ³
Acute - local effects, inhalation	260 mg/m ³
Long-term - systemic effects, oral	12.5 mg/kg bodyweight/day

QUIXX Paint

Safety Data Sheet

According to REACH Regulation (EC) No 1907/2006, as retained and amended in UK law

Long-term - systemic effects, inhalation	65.3 mg/m ³
Long-term - systemic effects, dermal	125 mg/kg bodyweight/day
Long-term - local effects, inhalation	65.3 mg/m ³
PNEC (Water)	
PNEC aqua (freshwater)	0.327 mg/l
PNEC aqua (marine water)	0.327 mg/l
PNEC aqua (intermittent, freshwater)	0.327 mg/l
PNEC (Sediment)	
PNEC sediment (freshwater)	12.46 mg/kg dwt
PNEC sediment (marine water)	12.46 mg/kg dwt
PNEC (Soil)	
PNEC soil	2.31 mg/kg dwt
PNEC (STP)	
PNEC sewage treatment plant	6.58 mg/l
Ethanol (64-17-5)	
DNEL/DMEL (Workers)	
Long-term - systemic effects, dermal	8238 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	380 mg/m ³
DNEL/DMEL (General population)	
Long-term - systemic effects, inhalation	114 mg/m ³
PNEC (Water)	
PNEC aqua (freshwater)	0.96 mg/l
PNEC aqua (marine water)	0.79 mg/l
PNEC aqua (intermittent, freshwater)	2.75 mg/l
PNEC (Sediment)	
PNEC sediment (freshwater)	3.6 mg/kg dwt
PNEC sediment (marine water)	2.9 mg/kg dwt
PNEC (Soil)	
PNEC soil	0.63 mg/kg dwt
PNEC (Oral)	
PNEC oral (secondary poisoning)	0.38 kg/kg food
PNEC (STP)	
PNEC sewage treatment plant	580 mg/l
2-methoxy-1-methylethyl acetate (108-65-6)	
DNEL/DMEL (Workers)	
Acute - local effects, inhalation	550 mg/m ³
Long-term - systemic effects, dermal	796 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	275 mg/m ³
DNEL/DMEL (General population)	
Acute - systemic effects, oral	500 mg/kg bodyweight/day

QUIXX Paint

Safety Data Sheet

According to REACH Regulation (EC) No 1907/2006, as retained and amended in UK law

Long-term - systemic effects, oral	36 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	33 mg/m ³
Long-term - systemic effects, dermal	320 mg/kg bodyweight/day
Long-term - local effects, inhalation	33 mg/m ³
PNEC (Water)	
PNEC aqua (freshwater)	0.635 mg/l
PNEC aqua (marine water)	0.064 mg/l
PNEC aqua (intermittent, freshwater)	6.35 mg/l
PNEC (Sediment)	
PNEC sediment (freshwater)	3.29 mg/kg dwt
PNEC sediment (marine water)	0.329 mg/kg dwt
PNEC (Soil)	
PNEC soil	0.29 mg/kg dwt
PNEC (STP)	
PNEC sewage treatment plant	100 mg/l
aluminium powder (stabilised) (7429-90-5)	
DNEL/DMEL (Workers)	
Long-term - systemic effects, inhalation	3.72 mg/m ³
Long-term - local effects, inhalation	3.72 mg/m ³
DNEL/DMEL (General population)	
Long-term - systemic effects, oral	3.95 mg/kg bodyweight/day
PNEC (STP)	
PNEC sewage treatment plant	20 mg/l
acetone (67-64-1)	
DNEL/DMEL (Workers)	
Acute - local effects, inhalation	2420 mg/m ³
Long-term - systemic effects, dermal	186 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	1210 mg/m ³
DNEL/DMEL (General population)	
Long-term - systemic effects, oral	62 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	200 mg/m ³
Long-term - systemic effects, dermal	62 mg/kg bodyweight/day
PNEC (Water)	
PNEC aqua (freshwater)	10.6 mg/l
PNEC aqua (marine water)	1.06 mg/l
PNEC aqua (intermittent, freshwater)	21 mg/l
PNEC (Sediment)	
PNEC sediment (freshwater)	30.4 mg/kg dwt
PNEC sediment (marine water)	3.04 mg/kg dwt

QUIXX Paint

Safety Data Sheet

According to REACH Regulation (EC) No 1907/2006, as retained and amended in UK law

PNEC (Soil)	
PNEC soil	29.5 mg/kg dwt
PNEC (STP)	
PNEC sewage treatment plant	100 mg/l
Naphtha (petroleum), hydrotreated heavy (64742-48-9)	
DNEL/DMEL (Workers)	
Acute - systemic effects, inhalation	1300 mg/m ³
Acute - local effects, inhalation	1100 mg/m ³
Long-term - systemic effects, inhalation	1.9 mg/m ³
Long-term - local effects, inhalation	840 mg/m ³
DNEL/DMEL (General population)	
Acute - systemic effects, inhalation	1200 mg/kg bodyweight/day
Acute - local effects, inhalation	640 mg/m ³
Long-term - systemic effects, inhalation	0.41 mg/m ³
Long-term - local effects, inhalation	180 mg/m ³
titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm] (13463-67-7)	
DNEL/DMEL (Workers)	
Long-term - local effects, inhalation	1.25 mg/m ³
DNEL/DMEL (General population)	
Long-term - local effects, inhalation	210 µg/m ³
propan-2-ol (67-63-0)	
DNEL/DMEL (Workers)	
Acute - systemic effects, inhalation	1000 mg/m ³
Long-term - systemic effects, dermal	888 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	500 mg/m ³
DNEL/DMEL (General population)	
Acute - systemic effects, inhalation	178 mg/m ³
Acute - systemic effects, oral	51 mg/kg bodyweight
Long-term - systemic effects, oral	26 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	89 mg/m ³
Long-term - systemic effects, dermal	319 mg/kg bodyweight/day
Carbon black (1333-86-4)	
DNEL/DMEL (Workers)	
Long-term - systemic effects, inhalation	1 mg/m ³
DNEL/DMEL (General population)	
Long-term - systemic effects, inhalation	60 µg/m ³
PNEC (Water)	
PNEC aqua (freshwater)	50 mg/l

QUIXX Paint

Safety Data Sheet

According to REACH Regulation (EC) No 1907/2006, as retained and amended in UK law

naphtha (petroleum), hydrodesulphurized heavy (64742-82-1)	
DNEL/DMEL (Workers)	
Acute - systemic effects, inhalation	1286 mg/m ³
Acute - local effects, inhalation	1066.67 mg/m ³
Long-term - systemic effects, inhalation	1.9 mg/m ³
Long-term - local effects, inhalation	837.5 mg/m ³
DNEL/DMEL (General population)	
Acute - systemic effects, inhalation	1152 mg/m ³
Acute - local effects, inhalation	640 mg/m ³
Long-term - systemic effects, inhalation	0.41 mg/m ³
Long-term - local effects, inhalation	178.57 mg/m ³

8.1.5. Control banding

No additional information available

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Appropriate engineering controls:

Ensure good ventilation of the work station.

8.2.2. Personal protection equipment

8.2.2.1. Eye and face protection

Eye protection:

Use splash goggles when eye contact due to splashing is possible. ISO 16321-1

8.2.2.2. Skin protection

Skin and body protection:

Wear suitable protective clothing. EN ISO 13688. EN 13034

Hand protection:

In case of repeated or prolonged contact wear gloves. ISO 374-1. Nitrile rubber. Choosing the proper glove is a decision that depends not only on the type of material, but also on other quality features, which differ for each manufacturer. Please follow the instructions related to the permeability and the penetration time provided by the manufacturer. Gloves must be replaced after each use and whenever signs of wear or perforation appear

8.2.2.3. Respiratory protection

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment. EN 143. Breathing apparatus with filter. A2/P3. . Breathing equipment is only to be used in order to handle the residual risk of short term jobs if all other risk minimizing measures have been carried out e.g. retention and/or local exhaust

8.2.2.4. Thermal hazards

No additional information available

8.2.3. Environmental exposure controls

Environmental exposure controls:

Avoid release to the environment.

Other information:

Do not eat, drink or smoke when using this product. Avoid contact with skin and eyes. Always wash hands after handling the product. The above mentioned instructions regarding the protective equipment refer to the industrial use of larger quantities.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid

QUIXX Paint

Safety Data Sheet

According to REACH Regulation (EC) No 1907/2006, as retained and amended in UK law

Colour	: Various colours.
Odour	: characteristic.
Odour threshold	: Not available
Melting point	: Not applicable
Freezing point	: Not available
Boiling point	: 124 °C
Flammability	: Not applicable
Explosive properties	: Product is not explosive. Explosive vapour/air mixtures may be formed.
Oxidising properties	: Non oxidizing.
Explosive limits	: Not available
Lower explosion limit	: 1.2 vol %
Upper explosion limit	: 15 vol %
Flash point	: 27 °C
Auto-ignition temperature	: 180 °C
Decomposition temperature	: Not available
pH	: Not available
Viscosity, kinematic	: Not available
Solubility	: Water: Not miscible
Partition coefficient n-octanol/water (Log Kow)	: Not available
Vapour pressure	: 58.7 hPa (20 °C)
Vapour pressure at 50°C	: Not available
Density	: 1 g/cm ³ (20 °C)
Relative density	: Not available
Relative vapour density at 20°C	: Not available
Particle characteristics	: Not applicable

9.2. Other information

9.2.1. Information with regard to physical hazard classes

No additional information available

9.2.2. Other safety characteristics

VOC content	: 64.5 %
Other properties	: Percent Solids,32.8 %

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport. Flammable liquid and vapour.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral) : Not classified (Based on available data, the classification criteria are not met)

QUIXX Paint

Safety Data Sheet

According to REACH Regulation (EC) No 1907/2006, as retained and amended in UK law

Acute toxicity (dermal) : Not classified (Based on available data, the classification criteria are not met)
Acute toxicity (inhalation) : Not classified (Based on available data, the classification criteria are not met)

QUIXX Paint	
ATE CLP (oral)	> 5000 mg/kg bodyweight
ATE CLP (vapours)	> 20 mg/l/4h

xylene	
LD50 oral rat	3523 mg/kg bodyweight (EU Method B.1)
LD50 dermal rabbit	1000 – 2000 mg/kg
LC50 Inhalation - Rat (Vapours)	29 mg/l/4h (EU Method B.2)

Skin corrosion/irritation : Not classified (Based on available data, the classification criteria are not met)
Serious eye damage/irritation : Not classified (Based on available data, the classification criteria are not met)
Respiratory or skin sensitisation : Not classified (Based on available data, the classification criteria are not met)
Germ cell mutagenicity : Not classified (Based on available data, the classification criteria are not met)
Carcinogenicity : Not classified (Based on available data, the classification criteria are not met)
Reproductive toxicity : Not classified (Based on available data, the classification criteria are not met)
STOT-single exposure : May cause drowsiness or dizziness.

n-butyl acetate (123-86-4)	
STOT-single exposure	May cause drowsiness or dizziness.

xylene	
STOT-single exposure	May cause respiratory irritation.

2-methoxy-1-methylethyl acetate (108-65-6)	
STOT-single exposure	May cause drowsiness or dizziness.

acetone (67-64-1)	
STOT-single exposure	May cause drowsiness or dizziness.

propan-2-ol (67-63-0)	
STOT-single exposure	May cause drowsiness or dizziness.

STOT-repeated exposure : Not classified (Based on available data, the classification criteria are not met)

xylene	
NOAEL (oral, rat, 90 days)	150 mg/kg bodyweight/day (OECD 408 method)
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.

naphtha (petroleum), hydrodesulphurized heavy (64742-82-1)	
STOT-repeated exposure	Causes damage to organs (central nervous system) through prolonged or repeated exposure.

Aspiration hazard : Not classified (Based on available data, the classification criteria are not met)

11.2. Information on other hazards

No additional information available

SECTION 12: Ecological information

12.1. Toxicity

Hazardous to the aquatic environment, short-term (acute) : Not classified (Based on available data, the classification criteria are not met)
Hazardous to the aquatic environment, long-term (chronic) : Not classified (Based on available data, the classification criteria are not met)

QUIXX Paint

Safety Data Sheet

According to REACH Regulation (EC) No 1907/2006, as retained and amended in UK law

Diiron trioxide	
EC50 72h algae	> 20 mg/l (72 h; Raphidocelis subcapitata; (OECD 201 method))
NOEC chronic crustacea	≥ 20 mg/l (21 d; Daphnia magna; (OECD 211 method))
NOEC chronic algae	≥ 20 mg/l (72 h; Raphidocelis subcapitata; (OECD 201 method))

12.2. Persistence and degradability

QUIXX Paint	
Persistence and degradability	The product has not been tested.

n-butyl acetate (123-86-4)	
Persistence and degradability	Readily biodegradable.
Biodegradation	83 % (28 d; (OECD 301D method))

xylene	
Persistence and degradability	Readily biodegradable.
Biodegradation	98 % (28d)

Ethanol (64-17-5)	
Persistence and degradability	Readily biodegradable.
Biodegradation	84 % (20 d)

2-methoxy-1-methylethyl acetate (108-65-6)	
Persistence and degradability	Readily biodegradable.
Biodegradation	90 – 99 % (28 d; (OECD 301F method))

acetone (67-64-1)	
Persistence and degradability	Readily biodegradable.
Biodegradation	90.9 % (28 d; (OECD 301B method))

titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm] (13463-67-7)	
Persistence and degradability	Not applicable for inorganic substances.

propan-2-ol (67-63-0)	
Persistence and degradability	Readily biodegradable.
Biodegradation	53 % (5 d ; Test method EU C.5)

Diiron trioxide (1309-37-1)	
Persistence and degradability	Not applicable for inorganic substances.

Carbon black (1333-86-4)	
Persistence and degradability	Not applicable for inorganic substances.

12.3. Bioaccumulative potential

QUIXX Paint	
Bioaccumulative potential	The product has not been tested.

n-butyl acetate (123-86-4)	
Bioconcentration factor (BCF REACH)	15 (Calculation method)
Partition coefficient n-octanol/water (Log Pow)	2.3 (25 °C; (OECD 117 method))

QUIXX Paint

Safety Data Sheet

According to REACH Regulation (EC) No 1907/2006, as retained and amended in UK law

Bioaccumulative potential	Slightly bioaccumulative.
xylene	
Partition coefficient n-octanol/water (Log Pow)	3.12 – 3.2
Bioaccumulative potential	Bioaccumulation unlikely.
Ethanol (64-17-5)	
Partition coefficient n-octanol/water (Log Kow)	-0.35 (20 °C)
Bioaccumulative potential	Bioaccumulation unlikely.
2-methoxy-1-methylethyl acetate (108-65-6)	
Partition coefficient n-octanol/water (Log Pow)	1.2 (20 °C; pH 6.8; (OECD 117 method))
Bioaccumulative potential	Bioaccumulation unlikely.
acetone (67-64-1)	
Bioconcentration factor (BCF REACH)	3 (calculated value)
Partition coefficient n-octanol/water (Log Pow)	-0.23 Quantitative structure-activity relationship (QSAR)
Bioaccumulative potential	Bioaccumulation unlikely.
titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm] (13463-67-7)	
Bioaccumulative potential	Not applicable for inorganic substances.
propan-2-ol (67-63-0)	
Partition coefficient n-octanol/water (Log Pow)	0.05 (25 °C)
Bioaccumulative potential	Bioaccumulation unlikely.
Diiron trioxide (1309-37-1)	
Partition coefficient n-octanol/water (Log Kow)	0.03
Bioaccumulative potential	Not applicable for inorganic substances.
Carbon black (1333-86-4)	
Bioaccumulative potential	Not applicable for inorganic substances.
12.4. Mobility in soil	
QUIXX Paint	
Ecology - soil	The product has not been tested.
n-butyl acetate (123-86-4)	
Surface tension	61.3 mN/m (20 °C; 1 g/L; (OECD 115 method))
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	1.268 – 1.844 (Quantitative structure-activity relationship (QSAR))
Ecology - soil	Product adsorbs little onto the soil.
xylene	
Surface tension	28 – 29.8 mN/m
Ethanol (64-17-5)	
Surface tension	22.31 mN/m (20 °C)
2-methoxy-1-methylethyl acetate (108-65-6)	
Surface tension	29.4 mN/m (20 °C)

QUIXX Paint

Safety Data Sheet

According to REACH Regulation (EC) No 1907/2006, as retained and amended in UK law

acetone (67-64-1)	
Surface tension	23.3 mN/m (20 °C)
Ecology - soil	Expected to be highly mobile in soil.
propan-2-ol (67-63-0)	
Ecology - soil	Expected to be highly mobile in soil.
Carbon black (1333-86-4)	
Ecology - soil	Not applicable.

12.5. Results of PBT and vPvB assessment

Component	
n-butyl acetate (123-86-4)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
xylene (1330-20-7)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
Ethanol (64-17-5)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
2-methoxy-1-methylethyl acetate (108-65-6)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
aluminium powder (stabilised) (7429-90-5)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
bis(2-ethylhexyl) adipate (103-23-1)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
acetone (67-64-1)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
Naphtha (petroleum), hydrotreated heavy (64742-48-9)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
Silicon dioxide (7631-86-9)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter $\leq 10 \mu\text{m}$] (13463-67-7)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
propan-2-ol (67-63-0)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
Diiron trioxide (1309-37-1)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
29H,31H-phthalocyaninato(2-)-N29,N30,N31,N32 copper (147-14-8)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
Carbon black (1333-86-4)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII

12.6. Endocrine disrupting properties

No additional information available

12.7. Other adverse effects

No additional information available

QUIXX Paint

Safety Data Sheet

According to REACH Regulation (EC) No 1907/2006, as retained and amended in UK law






SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods	: Disposal must be done according to official regulations. European waste catalogue. Do not discharge into drains or the environment. Do not dispose of with domestic waste.
Product/Packaging disposal recommendations	: Recycle or dispose of in compliance with current legislation.
Additional information	: Flammable vapours may accumulate in the container.
European List of Waste (LoW) code	: 08 01 11* - waste paint and varnish containing organic solvents or other dangerous substances
HP Code	: HP3 - "Flammable:" – flammable liquid waste: liquid waste having a flash point below 60 °C or waste gas oil, diesel and light heating oils having a flash point > 55 °C and ≤ 75 °C; – flammable pyrophoric liquid and solid waste: solid or liquid waste which, even in small quantities, is liable to ignite within five minutes after coming into contact with air; – flammable solid waste: solid waste which is readily combustible or may cause or contribute to fire through friction; – flammable gaseous waste: gaseous waste which is flammable in air at 20 °C and a standard pressure of 101.3 kPa; – water reactive waste: waste which, in contact with water, emits flammable gases in dangerous quantities; – other flammable waste: flammable aerosols, flammable self-heating waste, flammable organic peroxides and flammable self-reactive waste.

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

ADR	IMDG	IATA	ADN	RID
14.1. UN number or ID number				
UN 1263	UN 1263	UN 1263	UN 1263	UN 1263
14.2. UN proper shipping name				
PAINT	PAINT	Paint	PAINT	PAINT
Transport document description				
UN 1263 PAINT, 3, III, (D/E)	UN 1263 PAINT, 3, III	UN 1263 Paint, 3, III	UN 1263 PAINT, 3, III	UN 1263 PAINT, 3, III
14.3. Transport hazard class(es)				
3	3	3	3	3
				
14.4. Packing group				
III	III	III	III	III
14.5. Environmental hazards				
Dangerous for the environment: No	Dangerous for the environment: No Marine pollutant: No	Dangerous for the environment: No	Dangerous for the environment: No	Dangerous for the environment: No
No supplementary information available				

14.6. Special precautions for user

Overland transport

Classification code (ADR) : F1

QUIXX Paint

Safety Data Sheet

According to REACH Regulation (EC) No 1907/2006, as retained and amended in UK law

Special provisions (ADR) : 163, 367, 650
Limited quantities (ADR) : 5L
Excepted quantities (ADR) : E1
Transport category (ADR) : 3
Hazard identification number (Kemler No.) : 30
Orange plates :



Tunnel restriction code (ADR) : D/E
EAC code : •3Y

Transport by sea

Special provisions (IMDG) : 163, 223, 367, 955
Limited quantities (IMDG) : 5 L
Excepted quantities (IMDG) : E1
EmS-No. (Fire) : F-E
EmS-No. (Spillage) : S-E

Air transport

PCA Excepted quantities (IATA) : E1
PCA Limited quantities (IATA) : Y344
PCA limited quantity max net quantity (IATA) : 10L
PCA packing instructions (IATA) : 355
PCA max net quantity (IATA) : 60L
CAO max net quantity (IATA) : 220L
Special provisions (IATA) : A3, A72, A192

Inland waterway transport

Classification code (ADN) : F1
Special provisions (ADN) : 163, 367, 650
Limited quantities (ADN) : 5 L
Excepted quantities (ADN) : E1
Additional requirements/Remarks (ADN) :

Rail transport

Classification code (RID) : F1
Special provisions (RID) : 163, 367, 650
Limited quantities (RID) : 5L
Excepted quantities (RID) : E1
Transport category (RID) : 3
Hazard identification number (RID) : 30

14.7. Maritime transport in bulk according to IMO instruments

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

REACH Annex XVII (Restriction List)

EU restriction list (REACH Annex XVII)	
Reference code	Applicable on
3(a)	QUIXX Paint ; n-butyl acetate ; xylene ; Ethanol ; 2-methoxy-1-methylethyl acetate ; acetone ; naphtha (petroleum), hydrodesulphurized heavy
3(b)	QUIXX Paint ; n-butyl acetate ; xylene ; Ethanol ; 2-methoxy-1-methylethyl acetate ; acetone ; Naphtha (petroleum), hydrotreated heavy ; naphtha (petroleum), hydrodesulphurized heavy

QUIXX Paint

Safety Data Sheet

According to REACH Regulation (EC) No 1907/2006, as retained and amended in UK law

3(c)	naphtha (petroleum), hydrodesulphurized heavy
40.	n-butyl acetate ; xylene ; Ethanol ; 2-methoxy-1-methylethyl acetate ; aluminium powder (stabilised) ; acetone ; naphtha (petroleum), hydrodesulphurized heavy

REACH Annex XIV (Authorisation List)

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

REACH Candidate List (SVHC)

Contains no substance(s) listed on the REACH Candidate List

PIC Regulation (Prior Informed Consent)

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

POP Regulation (Persistent Organic Pollutants)

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

Ozone Regulation (1005/2009)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 1005/2009 on substances that deplete the ozone layer)

VOC Directive (2004/42)

VOC content : 64.5 %

Seveso Directive (Disaster Risk Reduction)

Seveso III Part I (Categories of dangerous substances)	Qualifying quantity (tonnes)	
	Lower-tier	Upper-tier
P5c FLAMMABLE LIQUIDS Flammable liquids, Categories 2 or 3 not covered by P5a and P5b	5000	50000

Explosives Precursors Regulation (2019/1148)

Contains substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

ANNEX II REPORTABLE EXPLOSIVES PRECURSORS

List of substances on their own or in mixtures or in substances for which suspicious transactions and significant disappearances and thefts are to be reported to the relevant national contact point within 24 hours.

Name	CAS-No.	Combined Nomenclature code (CN)	Combined Nomenclature code for mixture without constituents which would determine classification under another CN code
Acetone	67-64-1	2914 11 00	ex 3824 99 92
Aluminium, powders	7429-90-5	7603 10 00; ex 7603 20 00	

Please see https://ec.europa.eu/home-affairs/system/files/2021-11/list_of_competent_authorities_and_national_contact_points_en.pdf

Drug Precursors Regulation (273/2004)

Contains substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

Name	CN designation	CAS-No.	CN code	Category	Threshold	Annex
Acetone		67-64-1	2914 11 00	Category 3		Annex I

15.1.2. National regulations

No additional information available

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

QUIXX Paint

Safety Data Sheet

According to REACH Regulation (EC) No 1907/2006, as retained and amended in UK law

SECTION 16: Other information

Indication of changes			
Section	Changed item	Change	Comments
	General revision		
1.4	Emergency number	Modified	
2.2	Precautionary statements (CLP)	Modified	

Abbreviations and acronyms:	
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute Toxicity Estimate
BCF	Bioconcentration factor
CLP	Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008
DMEL	Derived Minimal Effect level
DNEL	Derived-No Effect Level
EC50	Median effective concentration
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
LC50	Median lethal concentration
LD50	Median lethal dose
LOAEL	Lowest Observed Adverse Effect Level
NOAEC	No-Observed Adverse Effect Concentration
NOAEL	No-Observed Adverse Effect Level
NOEC	No-Observed Effect Concentration
OECD	Organisation for Economic Co-operation and Development
PBT	Persistent Bioaccumulative Toxic
PNEC	Predicted No-Effect Concentration
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
SDS	Safety Data Sheet
STP	Sewage treatment plant
TLM	Median Tolerance Limit
vPvB	Very Persistent and Very Bioaccumulative
CAS-No.	Chemical Abstract Service number

Data sources

: European Chemicals Agency, <http://echa.europa.eu/>. Information provided by the manufacturer.

QUIXX Paint

Safety Data Sheet

According to REACH Regulation (EC) No 1907/2006, as retained and amended in UK law

Department issuing data specification sheet: : KFT Chemieservice GmbH
Im Leuschnerpark 3
D-64347 Griesheim

Phone: +49 6155-8981-400
Fax: +49 6155 8981-500
SDS Service: +49 6155 8981-522

Contact person : Victoria Bendt
Other information : Version/s 3.00 is/are not available in this language.

Full text of H- and EUH-statements:	
Acute Tox. 4 (Dermal)	Acute toxicity (dermal), Category 4
Acute Tox. 4 (Inhalation:vapour)	Acute toxicity (inhalation:vapour) Category 4
Aquatic Chronic 1	Hazardous to the aquatic environment – Chronic Hazard, Category 1
Asp. Tox. 1	Aspiration hazard, Category 1
Carc. 2	Carcinogenicity, Category 2
EUH066	Repeated exposure may cause skin dryness or cracking.
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Liq. 2	Flammable liquids, Category 2
Flam. Liq. 3	Flammable liquids, Category 3
Flam. Sol. 1	Flammable solids, Category 1
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H228	Flammable solid.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H351	Suspected of causing cancer.
H372	Causes damage to organs through prolonged or repeated exposure.
H373	May cause damage to organs through prolonged or repeated exposure.
H410	Very toxic to aquatic life with long lasting effects.
Skin Irrit. 2	Skin corrosion/irritation, Category 2
STOT RE 1	Specific target organ toxicity – Repeated exposure, Category 1
STOT RE 2	Specific target organ toxicity – Repeated exposure, Category 2
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Narcosis

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:		
Flam. Liq. 3	H226	On basis of test data
STOT SE 3	H336	Calculation method

QUIXX Paint

Safety Data Sheet

According to REACH Regulation (EC) No 1907/2006, as retained and amended in UK law

KFT SDS EU 11

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.