

Page 1/10

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 04.04.2024 Version number 3 (replaces version 2) Revision: 30.03.2022

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: SIMPLY SPRAYS BACKLIGHT SPRAY BLACK 400 ML
- · Article number: SP001
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

· Sector of Use

SU21 Consumer uses: Private households / general public / consumers

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

- · Product category Paint remover
- · Process category

PROC7 Industrial spraying

PROC11 Non industrial spraying

- · Application of the substance / the mixture Spray varnish
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

European Aerosols B.V.*

Wolfraamweg 2

NL-8471 XC Wolvega

The Netherlands

Tel: +31 (0)561 694400

e-mail: sds-nl@european-aerosols.com

- *Formerly known as Motip Dupli B.V.
- · Further information obtainable from: Department Product Safety
- 1.4 Emergency telephone number: +31 (0)561-694400 (09:00h - 17:00h)

UK: NPIS National Poisons Information Centre Tel: +44 0344 892 0111

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.



Eye Irrit. 2 H319

Causes serious eye irritation.

STOT SE 3 H336

May cause drowsiness or dizziness.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

(Contd. on page 2)

Printing date 04.04.2024 Version number 3 (replaces version 2) Revision: 30.03.2022

Trade name: SIMPLY SPRAYS BACKLIGHT SPRAY BLACK 400 ML

· Hazard pictograms





GHS02 GHS07

- · Signal word Danger
- · Hazard-determining components of labelling:

acetone

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics

· Hazard statements

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

H319 Causes serious eye irritation.H336 May cause drowsiness or dizziness.

· Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P260 Do not breathe spray.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of contents / container in accordance with regional regulations.

· Additional information:

EUH066 Repeated exposure may cause skin dryness or cracking.

Buildup of explosive mixtures possible without sufficient ventilation.

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

- 3.2 Mixtures
- · Description: Mixture of substances listed below with nonhazardous additions.

acetone Flam. Liq. 2, H225 Eye Irrit. 2, H319; STOT SE 3, H336 EUH066	25-<50%
propane Flam. Gas 1A, H220 Press. Gas (Comp.), H280	12.5-<20%
butane (containing < 0,1 % butadiene (203-450-8)) Flam. Gas IA, H220 Press. Gas (Comp.), H280	10-<12.5%
	♠ Flam. Liq. 2, H225 ♠ Eye Irrit. 2, H319; STOT SE 3, H336 EUH066 propane ♠ Flam. Gas 1A, H220 Press. Gas (Comp.), H280 butane (containing < 0,1 % butadiene (203-450-8)) ♠ Flam. Gas 1A, H220

GB

(Contd. of page 1)

Printing date 04.04.2024 Version number 3 (replaces version 2) Revision: 30.03.2022

Trade name: SIMPLY SPRAYS BACKLIGHT SPRAY BLACK 400 ML

_			
			(Contd. of page 2)
	EC number: 919-857-5 Reg.nr.: 01-2119463258-33	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics Flam. Liq. 3, H226 Asp. Tox. 1, H304 STOT SE 3, H336 EUH066	10-<12.5%
	CAS: 75-28-5 EINECS: 200-857-2 Index number: 601-004-00-0 Reg.nr.: 01-2119485395-27	isobutane (containing < 0,1 % butadiene (203-450-8)) Flam. Gas 1A, H220 Press. Gas (Comp.), H280	10-<12.5%
	CAS: 2457-02-5 EINECS: 219-536-3 Reg.nr.: 01-2120783571-49	strontium(II) 2-ethylhexanoate Repr. 1A, H360D Eye Dam. 1, H318 Acute Tox. 4, H302; Skin Irrit. 2, H315	<0.3%

· Additional information:

The content of Benzene (EINECS-Nr. 200-753-7) in the ingredients is less than 0,1% (Note P Annex 1A 1272/2008 EU), so the classification as carcinogen need not to apply. For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Generally the product does not irritate the skin.
- · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: Drink plenty of water and provide fresh air. Call for a doctor immediately.
- · 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- 4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents: Use fire extinguishing methods suitable to surrounding conditions.
- · 5.2 Special hazards arising from the substance or mixture

During heating or in case of fire poisonous gases are produced.

- · 5.3 Advice for firefighters -
- · Protective equipment: Mouth respiratory protective device.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation

Mount respiratory protective device.

Wear protective equipment. Keep unprotected persons away.

Keep away from ignition sources.

- 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · 6.3 Methods and material for containment and cleaning up:

Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation.

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

(Contd. on page 4)

Printing date 04.04.2024 Version number 3 (replaces version 2) Revision: 30.03.2022

Trade name: SIMPLY SPRAYS BACKLIGHT SPRAY BLACK 400 ML

(Contd. of page 3)

See Section 13 for disposal information.

SECTION 7: Handling and storage

- · 7.1 Precautions for safe handling Ensure good ventilation/exhaustion at the workplace.
- Information about fire and explosion protection:

Do not spray onto a naked flame or any incandescent material.

Keep ignition sources away - Do not smoke.

Keep respiratory protective device available.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles:

Observe official regulations on storing packagings with pressurised containers.

- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep container tightly sealed.
- · Storage class: 2 B
- · 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

PNEC 21 mg/l (Sporadic release)

· 8.1 Contro	l paran	neters
· Ingredient	s with l	imit values that require monitoring at the workplace:
67-64-1 ac	etone	
		value: 3620 mg/m³, 1500 ppm
_		value: 1210 mg/m³, 500 ppm
	•	(containing < 0,1 % butadiene (203-450-8))
		value: 1810 mg/m³, 750 ppm
		value: 1450 mg/m³, 600 ppm re than 0.1% of buta-1.3-diene)
	(ij moi	e than 0.176 of vuia-1.5-atene)
· DNELs		
67-64-1 ac		
Oral		62 mg/kg /per day (Consumer, longterm systemic)
Dermal	DNEL	62 mg/kg /per day (Consumer, longterm systemic)
	DNEL	186 mg/kg /per day (Worker, longterm systemic)
Inhalative	DNEL	2420 mg/m3 (Worker, acute local)
	DNEL	1210 mg/m3 (Worker, longterm systemic)
	DNEL	200 mg/m3 (Consumer, longterm systemic)
	DNEL	60 mg/m3
Hydrocarb	ons, C	2-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics
Oral	DNEL	125 mg/kg /per day (Consumer, longterm systemic)
Dermal	DNEL	208 mg/kg /per day (Worker, longterm systemic)
	DNEL	125 mg/kg /per day (Consumer, longterm systemic)
Inhalative	DNEL	871 mg/m3 (Worker, longterm systemic)
	DNEL	185 mg/m3 (Consumer, longterm systemic)
· PNECs		
67-64-1 ac	etone	
PNEC 10.	6 mg/l ((Freshwater)
PNEC 1.0	6 mg/l ((Seawater)

(Contd. on page 5)

Printing date 04.04.2024 Version number 3 (replaces version 2) Revision: 30.03.2022

Trade name: SIMPLY SPRAYS BACKLIGHT SPRAY BLACK 400 ML

(Contd. of page 4)

PNEC 100 mg/l (Sewage treatment plant)
PNEC 30.4 mg/kg (Freshwater sediment)
PNEC 3.04 mg/kg (Seawater sediment)
PNEC 29.5 mg/kg (Soil)

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Appropriate engineering controls No further data; see section 7.
- · Individual protection measures, such as personal protective equipment
- General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

 $Do \ not \ inhale \ gases \ / \ fumes \ / \ aerosols.$

Avoid contact with the eyes and skin.

Avoid contact with the eyes.

Respiratory protection:



In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Filter A2/P3

· Hand protection



Protective gloves

· Material of gloves

Butyl rubber, BR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

· Penetration time of glove material

Butyl rubber gloves with a thickness of 0.4 mm are resistant to:

Acetone: 480 min Butyl acetate: 60 min Ethyl acetate: 170 min

Xylene: 42 min

Butyl rubber gloves with a thickness of 0.4 mm are solvent resistant for 42-480 minutes. As protective measure, we recommend that users and responsible persons for work safety assume solvent resistance length of 42 minutes. Considering the data in section 3 of this SDS, one can assume longer resistance length in particular cases.

· Eye/face protection



Tightly sealed goggles

SECTION 9: Physical and chemical properties

- · 9.1 Information on basic physical and chemical properties
- General Information

Physical state
Colour:
Odour:
Solvent-like

· *Odour threshold:* Not determined.

(Contd. on page 6)

Printing date 04.04.2024 Version number 3 (replaces version 2) Revision: 30.03.2022

Trade name: SIMPLY SPRAYS BACKLIGHT SPRAY BLACK 400 ML

(Contd. of page 5) · Melting point/freezing point: Undetermined. · Boiling point or initial boiling point and boiling range Not applicable, as aerosol. · Flammability Not applicable. · Lower and upper explosion limit 0.6 Vol % (Hydrocarbons, C9-C11, n-alkanes, · Lower: isoalkanes, cyclics, <2% aromatics) · Upper: 13 Vol % (67-64-1 acetone) · Flash point: Not applicable, as aerosol. 240 °C (464 °F) (Hydrocarbons, C9-C11, n-alkanes, · Auto-ignition temperature: isoalkanes, cyclics, <2% aromatics) · Decomposition temperature: Not determined. $\cdot pH$ Mixture is non-soluble (in water). · Viscosity: · Kinematic viscosity Not determined. · Dynamic: Not determined. ·Solubility Not miscible or difficult to mix. · water: · Partition coefficient n-octanol/water (log value) Not determined. · Vapour pressure at 20 °C (68 °F): 3500 hPa (2625.2 mm Hg) · Density and/or relative density Density at 20 °C (68 °F): $0.7 \, \text{g/cm}^3 \, (5.8 \, \text{lbs/gal})$ · Relative density Not determined. · Vapour density Not determined. 9.2 Other information · Appearance: · Form: Aerosol · Important information on protection of health and environment, and on safety. Not determined. · Explosive properties: · Solvent content: 88.2 % · Organic solvents: · VOC (EC) 610.5 g/l 88.23 % · VOC-EU% 11.7% · Solids content: · Change in condition Not applicable. · Evaporation rate · Information with regard to physical hazard classes Void · Explosives · Flammable gases Void Extremely flammable aerosol. Pressurised container: · Aerosols May burst if heated. · Oxidising gases Void · Gases under pressure Void · Flammable liquids Void · Flammable solids Void · Self-reactive substances and mixtures Void · Pyrophoric liquids Void · Pyrophoric solids Void · Self-heating substances and mixtures Void · Substances and mixtures, which emit flammable gases in contact with water Void · Oxidising liquids Void · Oxidising solids Void · Organic peroxides Void · Corrosive to metals Void

(Contd. on page 7)

Printing date 04.04.2024 Version number 3 (replaces version 2) Revision: 30.03.2022

Trade name: SIMPLY SPRAYS BACKLIGHT SPRAY BLACK 400 ML

(Contd. of page 6)

· Desensitised explosives

Void

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

- · 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Acute toxicity Based on available data, the classification criteria are not met.

· <i>LD/LC50</i> 1	values releva	nt for classification:
67-64-1 ac	etone	
Oral	LD50	5800 mg/kg (rat)
Dermal	LD50	>15800 mg/kg (rabbit)
Inhalative	LC50 / 4h	76 mg/l (rat)
	LC50 / 96 h	5540 mg/l (oncorhynchus mykiss)
Hydrocarb	ons, C9-C11	, n-alkanes, isoalkanes, cyclics, <2% aromatics
Oral	LD50	>5000 mg/kg /per day (rat) (OECD 401)
Dermal	LD50	>2000 mg/kg (rat) (OECD 402)
Inhalative	LC50 / 4 h	>5000 mg/m3 (rat) (OECD 403)
2457-02-5	strontium(II	2-ethylhexanoate
Oral	LD50	2043 mg/kg (rat)
Dermal	LD50	>2000 mg/kg (rat)
Chin come	aion limmitatio	n No irritant effect

- · Skin corrosion/irritation No irritant effect.
- · Serious eye damage/irritation Causes serious eye irritation.
- · Respiratory or skin sensitisation No sensitising effects known.
- · STOT-single exposure May cause drowsiness or dizziness.
- · 11.2 Information on other hazards
- · Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

· 12.1 Toxicity

12.1 1021011	,
· Aquatic toxi	city:
67-64-1 acet	tone
LC50/96h	8300 mg/l (fish)
EC50/96h	7200 mg/l (algae)
LC50 / 48 h	8450 mg/l (crustacean (water flea))

- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.

(Contd. on page 8)

Printing date 04.04.2024 Version number 3 (replaces version 2) Revision: 30.03.2022

Trade name: SIMPLY SPRAYS BACKLIGHT SPRAY BLACK 400 ML

(Contd. of page 7)

- · 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · 12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

- · 12.7 Other adverse effects
- · Additional ecological information:
- · General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- · Recommendation:

Disposal must be made according to official regulations.

Disposal must be made according to official regulations.

14.1 UN number or ID number ADR, IMDG, IATA	UN1950
14.2 UN proper shipping name	
· ADR	1950 AEROSOLS
· IMDG	AEROSOLS
· IATA	AEROSOLS, flammable
· 14.3 Transport hazard class(es)	
· ADR	
· Class	2 5F Gases.
· Label	2.1
· IMDG, IATA	
· Class	2.1 Gases.
· Label	2.1
· 14.4 Packing group	
· ADR, IMDG, IATA	not regulated
· 14.5 Environmental hazards:	Not applicable.

(Contd. on page 9)

Printing date 04.04.2024 Version number 3 (replaces version 2) Revision: 30.03.2022

Trade name: SIMPLY SPRAYS BACKLIGHT SPRAY BLACK 400 ML

	(Contd. of page
EMS Number:	F-D,S-U
Stowage Code	SW1 Protected from sources of heat.
	SW22 For AEROSOLS with a maximum capacity of 1
	litre: Category A. For AEROSOLS with a capacity above
	1 litre: Category B. For WASTE AEROSOLS: Category
	C, Clear of living quarters.
Segregation Code	SG69 For AEROSOLS with a maximum capacity of 1
	litre:
	Segregation as for class 9. Stow "separated from" class
	except for division 1.4.
	For AEROSOLS with a capacity above 1 litre:
	Segregation as for the appropriate subdivision of class
	For WASTE AEROSOLS:
	Segregation as for the appropriate subdivision of class
14.7 Maritime transport in bulk accord	ling to IMO
instruments	Not applicable.
T	
Transport/Additional information:	
ADR	
	1L
ADR	1L Code: E0
ADR Limited quantities (LQ)	12
ADR Limited quantities (LQ) Excepted quantities (EQ) Transport category	Code: E0 Not permitted as Excepted Quantity 2
ADR Limited quantities (LQ) Excepted quantities (EQ)	Code: E0 Not permitted as Excepted Quantity
ADR Limited quantities (LQ) Excepted quantities (EQ) Transport category	Code: E0 Not permitted as Excepted Quantity 2
ADR Limited quantities (LQ) Excepted quantities (EQ) Transport category Tunnel restriction code	Code: E0 Not permitted as Excepted Quantity 2
ADR Limited quantities (LQ) Excepted quantities (EQ) Transport category Tunnel restriction code IMDG	Code: E0 Not permitted as Excepted Quantity 2 D
ADR Limited quantities (LQ) Excepted quantities (EQ) Transport category Tunnel restriction code IMDG Limited quantities (LQ)	Code: E0 Not permitted as Excepted Quantity 2 D
ADR Limited quantities (LQ) Excepted quantities (EQ) Transport category Tunnel restriction code IMDG Limited quantities (LQ)	Code: E0 Not permitted as Excepted Quantity 2 D IL Code: E0 Not permitted as Excepted Quantity Code: E0
ADR Limited quantities (LQ) Excepted quantities (EQ) Transport category Tunnel restriction code IMDG Limited quantities (LQ)	Code: E0 Not permitted as Excepted Quantity 2 D 1L Code: E0 Not permitted as Excepted Quantity

SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Poisons Act
- · Regulated explosives precursors

None of the ingredients is listed.

· Regulated poisons

None of the ingredients is listed.

· Reportable explosives precursors

67-64-1 acetone Listed

· Reportable poisons

None of the ingredients is listed.

- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P3a FLAMMABLE AEROSOLS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

Printing date 04.04.2024 Version number 3 (replaces version 2) Revision: 30.03.2022

Trade name: SIMPLY SPRAYS BACKLIGHT SPRAY BLACK 400 ML

(Contd. of page 9)

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

- H220 Extremely flammable gas.
- H225 Highly flammable liquid and vapour.
- H226 Flammable liquid and vapour.
- H280 Contains gas under pressure; may explode if heated.
- H302 Harmful if swallowed.
- H304 May be fatal if swallowed and enters airways.
- H315 Causes skin irritation.
- H318 Causes serious eye damage.
- H319 Causes serious eye irritation.
- H336 May cause drowsiness or dizziness.
- H360D May damage the unborn child.

EUH066 Repeated exposure may cause skin dryness or cracking.

· Classification according to Regulation (EC) No 1272/2008

Data is based on internal technical data and technical data from suppliers.

- · Department issuing SDS: R&D legislation and regulatory advisor
- · Contact: e-mail: sds-nl@european-aerosols.com
- · Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the

International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

DNEL: Derived No-Effect Level (UK REACH)

PNEC: Predicted No-Effect Concentration (UK REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Gas 1A: Flammable gases - Category 1A

Aerosol 1: Aerosols - Category 1

Press. Gas (Comp.): Gases under pressure – Compressed gas

Flam. Liq. 2: Flammable liquids – Category 2

Flam. Liq. 3: Flammable liquids - Category 3

Acute Tox. 4: Acute toxicity – Category 4

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation – Category 1

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Repr. 1A: Reproductive toxicity - Category 1A

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

Asp. Tox. 1: Aspiration hazard - Category 1

* * Data compared to the previous version altered.

GB