

Page 1/12

# Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 04.04.2024 Version number 73 (replaces version 72) Revision: 30.03.2022

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: SIMPLY SPRAYS MATT WHITE 500 ML
- · Article number: SP019
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

· Sector of Use

SU21 Consumer uses: Private households / general public / consumers

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

- · Product category Paint remover
- · Process category

PROC7 Industrial spraying

PROC11 Non industrial spraying

- · Application of the substance / the mixture Paint
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

European Aerosols B.V.\*

Wolfraamweg 2

NL-8471 XC Wolvega

The Netherlands

Tel: +31 (0)561 694400

e-mail: sds-nl@european-aerosols.com

- \*Formerly known as Motip Dupli B.V.
- · Further information obtainable from: Department Product Safety
- · 1.4 Emergency telephone number:

+31 (0)561-694400 (09:00h - 17:00h)

UK: NPIS National Poisons Information Centre Tel: +44 0344 892 0111

### SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.



Eye Irrit. 2 H319

Causes serious eye irritation.

STOT SE 3 H336

May cause drowsiness or dizziness.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

(Contd. on page 2)

Printing date 04.04.2024 Version number 73 (replaces version 72) Revision: 30.03.2022

Trade name: SIMPLY SPRAYS MATT WHITE 500 ML

### · Hazard pictograms





GHS02 GHS07

### · Signal word Danger

#### · Hazard-determining components of labelling:

acetone

n-butyl acetate

2-methoxy-1-methylethyl acetate

butan-1-ol

#### · Hazard statements

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

H319 Causes serious eye irritation.H336 May cause drowsiness or dizziness.

### Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

*P260* Do not breathe spray.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

*P501* Dispose of contents / container in accordance with regional regulations.

### Additional information:

EUH066 Repeated exposure may cause skin dryness or cracking.

Buildup of explosive mixtures possible without sufficient ventilation.

EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- $\cdot \textit{\textbf{PBT:}} \ \textit{Not applicable}.$
- · vPvB: Not applicable.

### SECTION 3: Composition/information on ingredients

- · 3.2 Mixtures
- · **Description:** Mixture of substances listed below with nonhazardous additions.

Dangerous components:		
CAS: 67-64-1 EINECS: 200-662-2 Index number: 606-001-00-8 Reg.nr.: 01-2119471330-49	acetone  Flam. Liq. 2, H225  Eye Irrit. 2, H319; STOT SE 3, H336  EUH066	25-<50%
CAS: 74-98-6 EINECS: 200-827-9 Index number: 601-003-00-5 Reg.nr.: 01-2119486944-21	propane Flam. Gas 1A, H220 Press. Gas (Comp.), H280	10-<12.5%
CAS: 123-86-4 EINECS: 204-658-1 Index number: 607-025-00-1 Reg.nr.: 01-2119485493-29	n-butyl acetate  Flam. Liq. 3, H226 STOT SE 3, H336 EUH066	10-<12.5%
CAS: 108-65-6 EINECS: 203-603-9 Index number: 607-195-00-7 Reg.nr.: 01-2119475791-29	2-methoxy-1-methylethyl acetate Flam. Liq. 3, H226 STOT SE 3, H336	5-<10%

GB

(Contd. of page 1)

Printing date 04.04.2024 Version number 73 (replaces version 72) Revision: 30.03.2022

Trade name: SIMPLY SPRAYS MATT WHITE 500 ML

		(Contd. of page
	butane (containing < 0,1 % butadiene (203-450-8))      Flam. Gas 1A, H220 Press. Gas (Comp.), H280	5-<10%
	isobutane (containing < 0,1 % butadiene (203-450-8))  Flam. Gas 1A, H220  Press. Gas (Comp.), H280	5-<10%
CAS: 13463-67-7 EINECS: 236-675-5 Index number: 022-006-00-2 Reg.nr.: 01-2119489379-17	titanium dioxide � Carc. 2, H351	2.5-<5%
CAS: 9004-70-0	cellulose nitrate  Expl. 1.1, H201	<2.5%
CAS: 71-36-3 EINECS: 200-751-6 Index number: 603-004-00-6 Reg.nr.: 01-2119484630-38	butan-1-ol Flam. Liq. 3, H226 Eye Dam. 1, H318 Acute Tox. 4, H302; Skin Irrit. 2, H315; STOT SE 3, H335-H336	≥1-<2.5%

#### · Additional information:

CAS 9004-70-0: GB CLP Note T

For the wording of the listed hazard phrases refer to section 16.

### SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Generally the product does not irritate the skin.
- · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: Drink plenty of water and provide fresh air. Call for a doctor immediately.
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- 4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

## SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents: Use fire extinguishing methods suitable to surrounding conditions.
- 5.2 Special hazards arising from the substance or mixture

  During heating or in case of fire poisonous gases are produced.
- 5.3 Advice for firefighters -
- · Protective equipment: Mouth respiratory protective device.

### SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation

Mount respiratory protective device.

Wear protective equipment. Keep unprotected persons away.

Keep away from ignition sources.

- 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · 6.3 Methods and material for containment and cleaning up:

Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation.

(Contd. on page 4)

Printing date 04.04.2024 Version number 73 (replaces version 72) Revision: 30.03.2022

Trade name: SIMPLY SPRAYS MATT WHITE 500 ML

(Contd. of page 3)

### · 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

# SECTION 7: Handling and storage

- · 7.1 Precautions for safe handling Ensure good ventilation/exhaustion at the workplace.
- · Information about fire and explosion protection:

Do not spray onto a naked flame or any incandescent material.

Keep ignition sources away - Do not smoke.

Keep respiratory protective device available.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles:

Observe official regulations on storing packagings with pressurised containers.

- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep container tightly sealed.
- · Storage class: 2 B
- · 7.3 Specific end use(s) No further relevant information available.

# SECTION 8: Exposure controls/personal protection

Ingre	dients with limit values that require monitoring at the workplace:
<b>67-6</b> 4	I-1 acetone
WEL	Short-term value: $3620 \text{ mg/m}^3$ , $1500 \text{ ppm}$ Long-term value: $1210 \text{ mg/m}^3$ , $500 \text{ ppm}$
123-8	6-4 n-butyl acetate
WEL	Short-term value: 966 mg/m³, 200 ppm Long-term value: 724 mg/m³, 150 ppm
108-6	5-6 2-methoxy-1-methylethyl acetate
WEL	Short-term value: 548 mg/m³, 100 ppm Long-term value: 274 mg/m³, 50 ppm Sk
106-9	7-8 butane (containing < 0,1 % butadiene (203-450-8))
WEL	Short-term value: $1810 \text{ mg/m}^3$ , $750 \text{ ppm}$ Long-term value: $1450 \text{ mg/m}^3$ , $600 \text{ ppm}$ Carc (if more than $0.1\%$ of buta-1.3-diene)
1346.	3-67-7 titanium dioxide
WEL	Long-term value: 10* 4** mg/m³ *total inhalable **respirable
71-36	6-3 butan-1-ol
WEL	Short-term value: 154 mg/m³, 50 ppm Sk

### 67-64-1 acetone

Oral	DNEL	62 mg/kg /per day (Consumer, longterm systemic)
Dermal	DNEL	62 mg/kg /per day (Consumer, longterm systemic)
	DNEL	186 mg/kg /per day (Worker, longterm systemic)
Inhalative	DNEL	2420 mg/m3 (Worker, acute local)

(Contd. on page 5)

Printing date 04.04.2024 Version number 73 (replaces version 72) Revision: 30.03.2022

Trade name: SIMPLY SPRAYS MATT WHITE 500 ML

		ontd. of pag
	DNEL 1210 mg/m3 (Worker, longterm systemic)	
	DNEL 200 mg/m3 (Consumer, longterm systemic)	
	DNEL 60 mg/m3	
	n-butyl acetate	
Oral	DNEL 2 mg/kg /per day (Consumer, longterm systemic)	
	DNEL 2 mg/kg /per day (Consumer, acute systemic)	
Dermal	DNEL 11 mg/kg /per day (Worker, longterm systemic)	
	DNEL 11 mg/kg/per day (Worker, acute systemic)	
	DNEL 6 mg/kg /per day (Consumer, longterm systemic)	
	DNEL 6 mg/kg /per day (Consumer, acute systemic)	
Inhalative	DNEL 300 mg/m3 (Worker, longterm systemic)	
	DNEL 600 mg/m3 (Worker, acute systemic)	
	DNEL 300 mg/m3 (Worker, longterm local)	
	DNEL 600 mg/m3 (Worker, acute local)	
	DNEL 35.7 mg/m3 (Consumer, longterm systemic)	
	DNEL 300 mg/m3 (Consumer; acute systemic)	
	DNEL 35.7 mg/m3 (Consumer, longterm local)	
	2-methoxy-1-methylethyl acetate	
Dermal	DNEL 796 mg/kg /per day (Worker, longterm systemic)	
	DNEL 320 mg/kg /per day (Consumer, longterm systemic)	
Inhalative	DNEL 275 mg/m3 (Worker, longterm systemic)	
<b>-</b> 1 2 4 2 1	DNEL 33 mg/m3 (Consumer, longterm systemic)	
	outan-1-ol	
Oral	DNEL 3.125 mg/kg /per day (Consumer, longterm systemic)	
Inhalative	DNEL 310 mg/m3 (Worker, longterm local)	
	DNEL   55 mg/m3 (Consumer, longterm local)	
· PNECs		
67-64-1 a		
	0.6 mg/l (Freshwater)	
	06 mg/l (Seawater)	
	l mg/l (Sporadic release)	
	00 mg/l (Sewage treatment plant)	
	0.4 mg/kg (Freshwater sediment)	
	04 mg/kg (Seawater sediment)	
	9.5 mg/kg (Soil)	
	n-butyl acetate	
	18 mg/l (Freshwater)	
PNEC 0.018 mg/l (Seawater)		
PNEC 0.36 mg/l (Sporadic release)		
PNEC 35.6 mg/l (Sewage treatment plant)		
	981 mg/kg (Freshwater sediment)	
	0981 mg/kg (Seawater sediment)	
	0903 mg/kg (Soil)	
	2-methoxy-1-methylethyl acetate	
	635 mg/l (Freshwater)	
$PNEC \mid 0$ .	064 mg/l (Seawater)	

Printing date 04.04.2024 Version number 73 (replaces version 72) Revision: 30.03.2022

Trade name: SIMPLY SPRAYS MATT WHITE 500 ML

		_
	(Contd. of page 5)	
PNEC	100 mg/l (Sewage treatment plant)	
PNEC	3.29 mg/kg (Freshwater sediment)	
PNEC	0.329 mg/kg (Seawater sediment)	
PNEC	0.29 mg/kg (Soil)	
71-36-	3 butan-1-ol	
PNEC	0.082 mg/l (Freshwater)	
PNEC	0.0082 mg/l (Seawater)	
PNEC	2.25 mg/l (Sporadic release)	
PNEC	2476 mg/l (Sewage treatment plant)	
PNEC	0.178 mg/kg (Freshwater sediment)	
PNEC	0.0178 mg/kg (Seawater sediment)	
PNEC	0.015 mg/kg (Soil)	

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Appropriate engineering controls No further data; see section 7.
- · Individual protection measures, such as personal protective equipment
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes and skin.

Avoid contact with the eyes.

· Respiratory protection:



In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Filter A2/P3

· Hand protection



Protective gloves

#### · Material of gloves

Butyl rubber, BR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

#### · Penetration time of glove material

Butyl rubber gloves with a thickness of 0.4 mm are resistant to:

Acetone: 480 min Butyl acetate: 60 min Ethyl acetate: 170 min

Xylene: 42 min

Butyl rubber gloves with a thickness of 0.4 mm are solvent resistant for 42- 480 minutes. As protective measure, we recommend that users and responsible persons for work safety assume solvent resistance length of 42 minutes. Considering the data in section 3 of this SDS, one can assume longer resistance length in particular cases.

(Contd. on page 7)

Printing date 04.04.2024 Version number 73 (replaces version 72) Revision: 30.03.2022

Trade name: SIMPLY SPRAYS MATT WHITE 500 ML

· Eye/face protection



Tightly sealed goggles

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

· Physical state Aerosol · Colour: White · Odour: Solvent-like Not determined. · Odour threshold: · Melting point/freezing point: Undetermined.

· Boiling point or initial boiling point and boiling

Not applicable, as aerosol. · Flammability Not applicable.

· Lower and upper explosion limit

1.2 Vol % (123-86-4 n-butyl acetate) · Lower:

13 Vol % (67-64-1 acetone) · Upper: Not applicable, as aerosol. · Flash point:

333 °C (631.4 °F) (108-65-6 2-methoxy-1-methylethyl · Auto-ignition temperature:

acetate)

· Decomposition temperature: Not determined.  $\cdot pH$ Not determined.

· Viscosity:

· Kinematic viscosity Not determined. · Dynamic: Not determined.

·Solubility

Not miscible or difficult to mix.

· Partition coefficient n-octanol/water (log value) Not determined.

· Vapour pressure at 20 °C (68 °F): 3500 hPa (2625.2 mm Hg)

· Density and/or relative density

· Density at 20 °C (68 °F):  $0.8 \, \text{g/cm}^3 \, (6.7 \, \text{lbs/gal})$ · Relative density Not determined.

· Vapour density Not determined.

· 9.2 Other information

· Appearance:

· Form: Aerosol

· Important information on protection of health and environment, and on safety.

• Explosive properties: Not determined.

· Solvent content:

· Organic solvents: 87.6 % · Water: 0.2 % · **VOC** (**EC**)  $720.7 \, g/l$ · VOC-EU% 87.55 % · Solids content: 8.2 %

· Change in condition

· Evaporation rate Not applicable.

· Information with regard to physical hazard classes

· Explosives Void

(Contd. on page 8)

(Contd. of page 6)

Printing date 04.04.2024 Version number 73 (replaces version 72) Revision: 30.03.2022

Trade name: SIMPLY SPRAYS MATT WHITE 500 ML

	(Contd. of page 7)
· Flammable gases	Void
· Aerosols	Extremely flammable aerosol. Pressurised container:
	May burst if heated.
· Oxidising gases	Void
· Gases under pressure	Void
· Flammable liquids	Void
· Flammable solids	Void
· Self-reactive substances and mixtures	Void
· Pyrophoric liquids	Void
· Pyrophoric solids	Void
· Self-heating substances and mixtures	Void
· Substances and mixtures, which emit flammable	
gases in contact with water	Void
Oxidising liquids	Void
· Oxidising solids	Void
· Organic peroxides	Void
· Corrosive to metals	Void
Desensitised explosives	Void

# SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

### SECTION 11: Toxicological information

- · 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Acute toxicity Based on available data, the classification criteria are not met.

		nt for classification:
67-64-1 ac	etone	
Oral	LD50	5800 mg/kg (rat)
Dermal	LD50	>15800 mg/kg (rabbit)
Inhalative	LC50 / 4h	76 mg/l (rat)
	LC50 / 96 h	5540 mg/l (oncorhynchus mykiss)
123-86-4 n	-butyl acetat	e
Oral	LD50	10800 mg/kg (rat) (OECD 401)
Dermal	LD50	>17600 mg/kg (rabbit)
Inhalative	LC50 / 4 h	>21 mg/m3 (rat)
108-65-6 2	-methoxy-1-	methylethyl acetate
Oral	LD50	8530 mg/kg (rat)
Dermal	LD50	>5000 mg/kg (rabbit)
Inhalative	LC50 / 4 h	>10000 mg/m3 (rat)
71-36-3 bu	tan-1-ol	
Oral	LD50	2292 mg/kg (rat)
Dermal	LD50	3430 mg/kg (rabbit)
Inhalative	LC50 / 4 h	17000 mg/m3 (rat)
		(Contd. on pag

-GB

Printing date 04.04.2024 Version number 73 (replaces version 72) Revision: 30.03.2022

Trade name: SIMPLY SPRAYS MATT WHITE 500 ML

(Contd. of page 8)

- · Skin corrosion/irritation No irritant effect.
- · Serious eye damage/irritation Causes serious eye irritation.
- · Respiratory or skin sensitisation No sensitising effects known.
- · STOT-single exposure May cause drowsiness or dizziness.
- · 11.2 Information on other hazards
- · Endocrine disrupting properties

None of the ingredients is listed.

### SECTION 12: Ecological information

· 12.1 Toxicity

40	uatic	tovi	cit	, .
лy	uuuu	ιυχι	uuv	٠.

### 67-64-1 acetone

LC50/96h 8300 mg/l (fish) EC50/96h 7200 mg/l (algae)

LC50 / 48 h 8450 mg/l (crustacean (water flea))

### 108-65-6 2-methoxy-1-methylethyl acetate

EC50/48 h > 500 mg/l (daphnia magna)

LC50 / 96 h 100-180 mg/l (oncorhynchus mykiss)

### 71-36-3 butan-1-ol

LC50/96 h 1376 mg/l (fish)

- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · 12.5 Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.
- · 12.6 Endocrine disrupting properties

*The product does not contain substances with endocrine disrupting properties.* 

- · 12.7 Other adverse effects
- · Additional ecological information:
- · General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

### **SECTION 13: Disposal considerations**

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- · Recommendation:

Disposal must be made according to official regulations.

Disposal must be made according to official regulations.

## SECTION 14: Transport information

- · 14.1 UN number or ID number
- · ADR, IMDG, IATA

UN1950

(Contd. on page 10)

Printing date 04.04.2024 Version number 73 (replaces version 72) Revision: 30.03.2022

Trade name: SIMPLY SPRAYS MATT WHITE 500 ML

	(Contd. of pag
14.2 UN proper shipping name	1050 AFRAGAIG
ADR IMDC	1950 AEROSOLS AEROSOLS
IMDG IATA	AEROSOLS AEROSOLS, flammable
14.3 Transport hazard class(es)	TEROSOES, Junimuote
ADR	
ADA	
Class Label	2 5F Gases. 2.1
IMDG, IATA	
Class Label	2.1 Gases. 2.1
	2.1
14.4 Packing group ADR, IMDG, IATA	not regulated
14.5 Environmental hazards:	Not applicable.
14.6 Special precautions for user	Warning: Gases.
Hazard identification number (Kemler code): EMS Number: Stowage Code Segregation Code 14.7 Maritime transport in bulk according to IM	F-D,S-U SW1 Protected from sources of heat. SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity about 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters. SG69 For AEROSOLS with a maximum capacity of 1 litre: Segregation as for class 9. Stow "separated from" class except for division 1.4. For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class
14.7 Maritime transport in bulk according to 11v. instruments	Not applicable.
Transport/Additional information:	
ADR	
Limited quantities (LQ)	1L
Excepted quantities (EQ)	Code: E0
Transport category	Not permitted as Excepted Quantity 2
Transport category Tunnel restriction code	$\stackrel{2}{D}$
IMDG	
IMDG Limited quantities (LO)	IL
IMDG Limited quantities (LQ) Excepted quantities (EQ)	1L Code: E0

Printing date 04.04.2024 Version number 73 (replaces version 72) Revision: 30.03.2022

Trade name: SIMPLY SPRAYS MATT WHITE 500 ML

		(Contd. of page 10)
	Not permitted as Excepted Quantity	
· UN ''Model Regulation'':	UN 1950 AEROSOLS, 2.1	

# SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Poisons Act
- · Regulated explosives precursors

None of the ingredients is listed.

· Regulated poisons

None of the ingredients is listed.

· Reportable explosives precursors

67-64-1 acetone Listed

· Reportable poisons

None of the ingredients is listed.

- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P3a FLAMMABLE AEROSOLS
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

#### SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- Relevant phrases
- H201 Explosive; mass explosion hazard.
- H220 Extremely flammable gas.
- H225 Highly flammable liquid and vapour.
- H226 Flammable liquid and vapour.
- H280 Contains gas under pressure; may explode if heated.
- H302 Harmful if swallowed.
- H315 Causes skin irritation.
- H318 Causes serious eye damage.
- H319 Causes serious eye irritation.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.
- H351 Suspected of causing cancer.

EUH066 Repeated exposure may cause skin dryness or cracking.

· Classification according to Regulation (EC) No 1272/2008

Data is based on internal technical data and technical data from suppliers.

- · Department issuing SDS: R&D legislation and regulatory advisor
- · Contact: e-mail: sds-nl@european-aerosols.com
- · Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

(Contd. on page 12)

Version number 73 (replaces version 72) Revision: 30.03.2022 Printing date 04.04.2024

Trade name: SIMPLY SPRAYS MATT WHITE 500 ML

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

DNEL: Derived No-Effect Level (UK REACH)

PNEC: Predicted No-Effect Concentration (UK REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative

Expl. 1.1: Explosives – Division 1.1

Flam. Gas 1A: Flammable gases - Category 1A

Aerosol 1: Aerosols – Category 1

Press. Gas (Comp.): Gases under pressure - Compressed gas

Flam. Liq. 2: Flammable liquids - Category 2 Flam. Liq. 3: Flammable liquids – Category 3

Acute Tox. 4: Acute toxicity - Category 4

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation - Category 1 Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Carc. 2: Carcinogenicity – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

\* \* Data compared to the previous version altered.

(Contd. of page 11)