

Page 1/12

*

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 04.04.2024

Version number 208 (replaces version 207)

Revision: 30.03.2022

Article number: SP022	SPRAYS GLOSSY BLACK 500 ML
	uses of the substance or mixture and uses advised against
No further relevant info	ormation available.
Sector of Use	
	Private households / general public / consumers
	es: Public domain (administration, education, entertainment, services, craftsmen)
Product category Paint	remover
Process category	
PROC7 Industrial spra	
PROC11 Non industrie	
Application of the subs	tance / the mixture Spray varnish
	lier of the safety data sheet
Manufacturer/Supplier	
European Aerosols B.V.	· *
Wolfraamweg 2	
NL-8471 XC Wolvega	
The Netherlands	
Tel: +31 (0)561 69440	
e-mail: sds-nl@europea	in-aerosois.com
*Formerly known as Mo	otin Dunli B.V.
	btainable from: Department Product Safety
1.4 Emergency telephon	
+31 (0)561-694400 (09	(00n - 1)(00n)
UK: NPIS National Poi	isons Information Centre Tel: +44 0344 892 0111
	5
SECTION 2: Hazai	rds identification
2.1 Classification of the	e substance or mixture
	g to Regulation (EC) No 1272/2008
^	5 10 Regulation (110) 110 12/2000
flame	
June	
Aerosol 1 H222-H229	9 Extremely flammable aerosol. Pressurised container: May burst if heated.
$\mathbf{\Lambda}$	
(1)	
\mathbf{V}	
V	Causas serious que invitation
Enalumit 2 11210	Causes serious eye irritation.
Eye Irrit. 2 H319	-
Eye Irrit. 2 H319 STOT SE 3 H336	May cause drowsiness or dizziness.
•	-

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 04.04.2024

Version number 208 (replaces version 207)

Revision: 30.03.2022

Trade name: SIMPLY SPRAYS GLOSSY BLACK 500 ML

	(Contd. of page
Hazard p	ictograms
$\mathbf{\wedge}$	∧
JH2	
<u></u>	
GHS02	GHS07
011502	011307
Signal w	ord Danger
Hazard-a	letermining components of labelling:
acetone	
n-butyl a	cetate
2-methox	y-1-methylethyl acetate
butan-1-	ol
Hazard s	tatements
H222-H2	29 Extremely flammable aerosol. Pressurised container: May burst if heated.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
Precautio	onary statements
P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking
P211	Do not spray on an open flame or other ignition source.
P251	Do not pierce or burn, even after use.
P260	Do not breathe spray.
P410+P4	12 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
P501	Dispose of contents / container in accordance with regional regulations.
Addition	al information:
EUH066	Repeated exposure may cause skin dryness or cracking.
Buildup o	of explosive mixtures possible without sufficient ventilation.
2.3 Other	r hazards
	f PBT and vPvB assessment

- **PBT:** Not applicable.
- · vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

×

· Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:

Dangerous components:				
CAS: 67-64-1	acetone	25-<50%		
EINECS: 200-662-2	🚸 Flam. Liq. 2, H225			
	🚯 Eye Irrit. 2, H319; STOT SE 3, H336			
Reg.nr.: 01-2119471330-49	EUH066			
CAS: 123-86-4	n-butyl acetate	12.5-<20%		
EINECS: 204-658-1	🚸 Flam. Liq. 3, H226			
Index number: 607-025-00-1				
Reg.nr.: 01-2119485493-29	EUH066			
CAS: 74-98-6	propane	10-<12.5%		
EINECS: 200-827-9	🚸 Flam. Gas 1A, H220			
Index number: 601-003-00-5	Press. Gas (Comp.), H280			
Reg.nr.: 01-2119486944-21				
	•	(Contd. on page 3		

according to Regulation (EC) No 1907/2006, Article 31

Printing date 04.04.2024

Version number 208 (replaces version 207)

Revision: 30.03.2022

Trade name: SIMPLY SPRAYS GLOSSY BLACK 500 ML

		Contd. of page 2
CAS: 108-65-6 EINECS: 203-603-9 Index number: 607-195-00-7 Reg.nr.: 01-2119475791-29	2-methoxy-1-methylethyl acetate Flam. Liq. 3, H226 STOT SE 3, H336	5-<10%
CAS: 106-97-8 EINECS: 203-448-7 Index number: 601-004-00-0 Reg.nr.: 01-2119474691-32	butane (containing < 0,1 % butadiene (203-450-8)) Flam. Gas IA, H220 Press. Gas (Comp.), H280	5-<10%
CAS: 75-28-5 EINECS: 200-857-2 Index number: 601-004-00-0 Reg.nr.: 01-2119485395-27	isobutane (containing < 0,1 % butadiene (203-450-8)) Flam. Gas IA, H220 Press. Gas (Comp.), H280	5-<10%
CAS: 9004-70-0	cellulose nitrate	<2.5%
CAS: 71-36-3 EINECS: 200-751-6 Index number: 603-004-00-6 Reg.nr.: 01-2119484630-38	butan-1-ol Flam. Liq. 3, H226 Eye Dam. 1, H318 Acute Tox. 4, H302; Skin Irrit. 2, H315; STOT SE 3, H335- H336	≥1-<2.5%
CAS: 67-63-0 EINECS: 200-661-7 Index number: 603-117-00-0 Reg.nr.: 01-2119457558-25	propan-2-ol Flam. Liq. 2, H225 Eye Irrit. 2, H319; STOT SE 3, H336	<2.5%

CAS 9004-70-0: GB CLP Note T

SECTION 4: First aid measures

• 4.1 Description of first aid measures

- After inhalation: Supply fresh air; consult doctor in case of complaints.
- After skin contact: Generally the product does not irritate the skin.
- After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- After swallowing: Drink plenty of water and provide fresh air. Call for a doctor immediately.
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

- 5.1 Extinguishing media
- Suitable extinguishing agents: Use fire extinguishing methods suitable to surrounding conditions.
- 5.2 Special hazards arising from the substance or mixture
- During heating or in case of fire poisonous gases are produced.
- · 5.3 Advice for firefighters -
- · Protective equipment: Mouth respiratory protective device.

SECTION 6: Accidental release measures

• 6.1 Personal precautions, protective equipment and emergency procedures Mount respiratory protective device. Wear protective equipment. Keep unprotected persons away. Keep away from ignition sources.

(Contd. on page 4)

For the wording of the listed hazard phrases refer to section 16.

GB

according to Regulation (EC) No 1907/2006, Article 31

Printing date 04.04.2024

Version number 208 (replaces version 207)

Revision: 30.03.2022

Trade name: SIMPLY SPRAYS GLOSSY BLACK 500 ML

(Contd. of page 3) • 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water. · 6.3 Methods and material for containment and cleaning up: Dispose contaminated material as waste according to section 13. Ensure adequate ventilation. · 6.4 Reference to other sections See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment. See Section 13 for disposal information. SECTION 7: Handling and storage • 7.1 Precautions for safe handling Ensure good ventilation/exhaustion at the workplace. · Information about fire - and explosion protection: Do not spray onto a naked flame or any incandescent material. Keep ignition sources away - Do not smoke. Keep respiratory protective device available. · 7.2 Conditions for safe storage, including any incompatibilities · Storage: • Requirements to be met by storerooms and receptacles: Observe official regulations on storing packagings with pressurised containers. · Information about storage in one common storage facility: Not required. • Further information about storage conditions: Keep container tightly sealed. · Storage class: 2 B · 7.3 Specific end use(s) No further relevant information available. SECTION 8: Exposure controls/personal protection · 8.1 Control parameters · Ingredients with limit values that require monitoring at the workplace: 67-64-1 acetone WEL Short-term value: 3620 mg/m³, 1500 ppm Long-term value: 1210 mg/m³, 500 ppm 123-86-4 n-butyl acetate WEL Short-term value: 966 mg/m³, 200 ppm Long-term value: 724 mg/m³, 150 ppm 108-65-6 2-methoxy-1-methylethyl acetate WEL Short-term value: 548 mg/m³, 100 ppm Long-term value: 274 mg/m³, 50 ppm Sk 106-97-8 butane (containing < 0,1 % butadiene (203-450-8)) WEL Short-term value: 1810 mg/m³, 750 ppm Long-term value: 1450 mg/m³, 600 ppm Carc (if more than 0.1% of buta-1.3-diene) 71-36-3 butan-1-ol WEL Short-term value: 154 mg/m³, 50 ppm Sk 67-63-0 propan-2-ol WEL Short-term value: 1250 mg/m³, 500 ppm Long-term value: 999 mg/m³, 400 ppm · DNELs 67-64-1 acetone Oral DNEL 62 mg/kg /per day (Consumer, longterm systemic)

(Contd. on page 5)

⁻ GB

Page 5/12

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 04.04.2024

Version number 208 (replaces version 207)

Revision: 30.03.2022

Trade name: SIMPLY SPRAYS GLOSSY BLACK 500 ML

D 1	DNEL		(Contd. of pag
Dermal		62 mg/kg /per day (Consumer, longterm systemic)	
		186 mg/kg /per day (Worker, longterm systemic)	
Inhalative		2420 mg/m3 (Worker, acute local)	
		1210 mg/m3 (Worker, longterm systemic)	
		200 mg/m3 (Consumer, longterm systemic)	
		60 mg/m3	
123-86-4 n	-		
Oral		2 mg/kg /per day (Consumer, longterm systemic)	
		2 mg/kg /per day (Consumer, acute systemic)	
Dermal		11 mg/kg /per day (Worker, longterm systemic)	
		11 mg/kg /per day (Worker, acute systemic)	
		6 mg/kg /per day (Consumer, longterm systemic)	
		6 mg/kg /per day (Consumer, acute systemic)	
Inhalative		300 mg/m3 (Worker, longterm systemic)	
		600 mg/m3 (Worker, acute systemic)	
		300 mg/m3 (Worker, longterm local)	
		600 mg/m3 (Worker, acute local)	
		35.7 mg/m3 (Consumer, longterm systemic)	
	DNEL	300 mg/m3 (Consumer; acute systemic)	
	DNEL	35.7 mg/m3 (Consumer, longterm local)	
108-65-6 2		xy-1-methylethyl acetate	
Dermal	DNEL	796 mg/kg /per day (Worker, longterm systemic)	
		320 mg/kg /per day (Consumer, longterm systemic)	
Inhalative	DNEL	275 mg/m3 (Worker, longterm systemic)	
		33 mg/m3 (Consumer, longterm systemic)	
71-36-3 bı			
Oral		3.125 mg/kg /per day (Consumer, longterm systemic)	
Inhalative		310 mg/m3 (Worker, longterm local)	
		55 mg/m3 (Consumer, longterm local)	
67-63-0 pr	-		
Oral		26 mg/kg /per day (Consumer, longterm systemic)	
Dermal		888 mg/kg /per day (Worker, longterm systemic)	
	DNEL	319 mg/kg /per day (Consumer, longterm systemic)	
Inhalative		500 mg/m3 (Worker, longterm systemic)	
	DNEL	89 mg/m3 (Consumer, longterm systemic)	
PNECs			
67-64-1 ac	etone		
PNEC 10.	6 mg/l (Freshwater)	
PNEC 1.0	6 mg/l (Seawater)	
PNEC 21	mg/l (Sp	poradic release)	
PNEC 100) mg/l (1	Sewage treatment plant)	
		(Freshwater sediment)	
		(Seawater sediment)	
PNEC 29.			
123-86-4 n			
PNEC 0.1	8 mg/l (Freshwater)	

Page 6/12

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 04.04.2024

Version number 208 (replaces version 207)

Revision: 30.03.2022

Trade name: SIMPLY SPRAYS GLOSSY BLACK 500 ML

	(Contd. of page 5)
PNEC	0.018 mg/l (Seawater)
PNEC	0.36 mg/l (Sporadic release)
PNEC	35.6 mg/l (Sewage treatment plant)
PNEC	0.981 mg/kg (Freshwater sediment)
PNEC	0.0981 mg/kg (Seawater sediment)
PNEC	0.0903 mg/kg (Soil)
108-65	5-6 2-methoxy-1-methylethyl acetate
PNEC	0.635 mg/l (Freshwater)
PNEC	0.064 mg/l (Seawater)
PNEC	100 mg/l (Sewage treatment plant)
PNEC	3.29 mg/kg (Freshwater sediment)
PNEC	0.329 mg/kg (Seawater sediment)
	0.29 mg/kg (Soil)
	-3 butan-1-ol
	0.082 mg/l (Freshwater)
	0.0082 mg/l (Seawater)
	2.25 mg/l (Sporadic release)
	2476 mg/l (Sewage treatment plant)
	0.178 mg/kg (Freshwater sediment)
PNEC	0.0178 mg/kg (Seawater sediment)
PNEC	0.015 mg/kg (Soil)
	0 propan-2-ol
	140.9 mg/l (Freshwater)
PNEC	140.9 mg/l (Seawater)
	140.9 mg/l (Sporadic release)
	2251 mg/l (Sewage treatment plant)
	552 mg/kg (Freshwater sediment)
	552 mg/kg (Seawater sediment)
· Additi	onal information: The lists valid during the making were used as basis.
	posure controls
	priate engineering controls No further data; see section 7. dual protection measures, such as personal protective equipment
	al protection measures, such as personal protective equipment al protective and hygienic measures:
Keep a	away from foodstuffs, beverages and feed.
	liately remove all soiled and contaminated clothing
	hands before breaks and at the end of work. t inhale gases / fumes / aerosols.
	contact with the eyes and skin.
	contact with the eyes.
· Respir	ratory protection:
6	In case of brief exposure or low pollution use respiratory filter device. In case of intensive or
	longer exposure use self-contained respiratory protective device.
Filter . • Hand	A2/P3 protection
đ	-
Mas-	Protective gloves

according to Regulation (EC) No 1907/2006, Article 31

Printing date 04.04.2024

Version number 208 (replaces version 207)

Revision: 30.03.2022

(Contd. of page 6)

Trade name: SIMPLY SPRAYS GLOSSY BLACK 500 ML

• *Material of gloves Butyl rubber, BR*

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

• Penetration time of glove material

Butyl rubber gloves with a thickness of 0.4 mm are resistant to: Acetone: 480 min Butyl acetate: 60 min Ethyl acetate: 170 min

Xylene: 42 min

Butyl rubber gloves with a thickness of 0.4 mm are solvent resistant for 42- 480 minutes. As protective measure, we recommend that users and responsible persons for work safety assume solvent resistance length of 42 minutes. Considering the data in section 3 of this SDS, one can assume longer resistance length in particular cases.

• Eye/face protection



Tightly sealed goggles

SECTION 9: Physical and chemical properties

•9.1 Information on basic physical and chemical p	roperties
· General Information	
· Physical state	Aerosol
· Colour:	Black
· Odour:	Solvent-like
• Odour threshold:	Not determined.
• Melting point/freezing point:	Undetermined.
· Boiling point or initial boiling point and boiling	
range	Not applicable, as aerosol.
· Flammability	Not applicable.
Lower and upper explosion limit	
· Lower:	1.2 Vol % (123-86-4 n-butyl acetate)
· Upper:	13 Vol % (67-64-1 acetone)
· Flash point:	Not applicable, as aerosol.
· Auto-ignition temperature:	333 °C (631.4 °F) (108-65-6 2-methoxy-1-methylethyl
	acetate)
· Decomposition temperature:	Not determined.
· pH	Mixture is non-soluble (in water).
Viscosity:	
Kinematic viscosity	Not determined.
Dynamic:	Not determined.
· Solubility	
· water:	Not miscible or difficult to mix.
• Partition coefficient n-octanol/water (log value)	Not determined.
· Vapour pressure at 20 °C (68 °F):	3500 hPa (2625.2 mm Hg)
Density and/or relative density	
Density at 20 °C (68 °F):	0.7 g/cm ³ (5.8 lbs/gal)
Relative density	Not determined.
· Vapour density	Not determined.
• 9.2 Other information	
· Appearance:	
· Form:	Aerosol
	(Contd. on page 8

according to Regulation (EC) No 1907/2006, Article 31

Printing date 04.04.2024

Version number 208 (replaces version 207)

Revision: 30.03.2022

Trade name: SIMPLY SPRAYS GLOSSY BLACK 500 ML

	(Contd. of pag
Important information on protection of heal	th and
environment, and on safety.	
Explosive properties:	Not determined.
Solvent content:	
Organic solvents:	91.9 %
Water:	0.3 %
VOC (EC)	
	683.6 g/l
VOC-EU%	91.93 %
Solids content:	7.6 %
Change in condition	
Evaporation rate	Not applicable.
Information with regard to physical hazard of	classes
Explosives	Void
Flammable gases	Void
Aerosols	Extremely flammable aerosol. Pressurised container:
	May burst if heated.
Oxidising gases	Void
Gases under pressure	Void
Flammable liquids	Void
Flammable solids	Void
Self-reactive substances and mixtures	Void
Pyrophoric liquids	Void
Pyrophoric solids	Void
Self-heating substances and mixtures	Void
Substances and mixtures, which emit flamm	able
gases in contact with water	Void
Oxidising liquids	Void
Oxidising solids	Void
Organic peroxides	Void
Corrosive to metals	Void
Desensitised explosives	Void

SECTION 10: Stability and reactivity

· 10.1 Reactivity No further relevant information available.

· 10.2 Chemical stability

- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

· 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

• Acute toxicity Based on available data, the classification criteria are not met.

67-64-1 acetone			
Oral	LD50	5800 mg/kg (rat)	
Dermal	LD50	>15800 mg/kg (rabbit)	
Inhalative		76 mg/l (rat)	
	LC50 / 96 h	5540 mg/l (oncorhynchus mykiss)	

(Contd. on page 9)

GB -

Page 9/12

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 04.04.2024

Version number 208 (replaces version 207)

Revision: 30.03.2022

Trade name: SIMPLY SPRAYS GLOSSY BLACK 500 ML

		(Contd. of page 8
123-86-4 n-butyl acetate		
Oral	LD50	10800 mg/kg (rat) (OECD 401)
Dermal	LD50	>17600 mg/kg (rabbit)
Inhalative	LC50 / 4 h	>21 mg/m3 (rat)
108-65-62	-methoxy-1-	methylethyl acetate
Oral	LD50	8530 mg/kg (rat)
Dermal	LD50	>5000 mg/kg (rabbit)
Inhalative	LC50 / 4 h	>10000 mg/m3 (rat)
71-36-3 bi	tan-1-ol	
Oral	LD50	2292 mg/kg (rat)
Dermal	LD50	3430 mg/kg (rabbit)
Inhalative	LC50 / 4 h	17000 mg/m3 (rat)
67-63-0 propan-2-ol		
Oral	LD50	5840 mg/kg (rat)
Dermal	LD50	13900 mg/kg (rabbit)
Inhalative	LC50	>25 mg/l (rat) LC 50: 6h
· Serious ey	e damage/irr	n No irritant effect. itation Causes serious eye irritation. sitisation No sensitising effects known

Respiratory or skin sensitisation No sensitising effects known.

· STOT-single exposure May cause drowsiness or dizziness.

· 11.2 Information on other hazards

· Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

· 12.1 Toxicity	
-----------------	--

· 12.1 Toxicity			
· Aquatic toxicity:			
67-64-1 acet	one		
LC50/96h	8300 mg/l (fish)		
EC50/96h	7200 mg/l (algae)		
LC50 / 48 h	8450 mg/l (crustacean (water flea))		
108-65-6 2-methoxy-1-methylethyl acetate			
EC50 / 48 h	>500 mg/l (daphnia magna)		
LC50 / 96 h	100-180 mg/l (oncorhynchus mykiss)		
71-36-3 butan-1-ol			
LC50 / 96 h	1376 mg/l (fish)		
67-63-0 propan-2-ol			
LC50/96h	9640 mg/l (pimephales promelas; 96h)		
LC50 / 24 h	9714 mg/l (daphnia magna)		
• 12.2 Persistence and degradability No further relevant information available.			
· 12.3 Bioaccumulative potential No further relevant information available.			
• 12.4 Mobility in soil No further relevant information available.			
• 12.5 Results of PBT and vPvB assessment			
• <i>PBT</i> : Not applicable.			
· vPvR· Not applicable			

• **vPvB**: Not applicable.

· 12.6 Endocrine disrupting properties The product does not contain substances with endocrine disrupting properties.

(Contd. on page 10)

GB

Page 10/12

*

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 04.04.2024

Version number 208 (replaces version 207)

Revision: 30.03.2022

Trade name: SIMPLY SPRAYS GLOSSY BLACK 500 ML

(Contd. of page 9)

- · 12.7 Other adverse effects
- \cdot Additional ecological information:
- General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

· Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· Uncleaned packaging:

Disposal must be made according to official regulations. Disposal must be made according to official regulations.

SECTION 14: Transport information

· 14.1 UN number or ID number · ADR, IMDG, IATA	UN1950
· 14.2 UN proper shipping name · ADR	1950 AEROSOLS
·IMDG	AEROSOLS
· IATA	AEROSOLS, flammable
· 14.3 Transport hazard class(es)	
· ADR	
· Class	2 5F Gases.
· Label	2.1
· IMDG, IATA	
· Class	2.1 Gases.
· Label	2.1
· 14.4 Packing group	
· ADR, IMDĞ, IATA	not regulated
· 14.5 Environmental hazards:	Not applicable.
· 14.6 Special precautions for user	Warning: Gases.
· Hazard identification number (Kemler code):	-
· EMS Number:	<i>F-D,S-U</i>
	(Contd. on page 1

[·] Recommendation:

Page 11/12

Printing date 04.04.2024

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Version number 208 (replaces version 207)

Revision: 30.03.2022

Trade name: SIMPLY SPRAYS GLOSSY BLACK 500 ML

	(Contd. of page 1
Stowage Code	SW1 Protected from sources of heat.
	SW22 For AEROSOLS with a maximum capacity of 1
	litre: Category A. For AEROSOLS with a capacity abov
	1 litre: Category B. For WASTE AEROSOLS: Category
	C, Clear of living quarters.
Segregation Code	SG69 For AEROSOLS with a maximum capacity of 1
0 0	litre:
	Segregation as for class 9. Stow "separated from" class
	except for division 1.4.
	For AEROSOLS with a capacity above 1 litre:
	Segregation as for the appropriate subdivision of class 2
	For WASTE AEROSOLS:
	Segregation as for the appropriate subdivision of class 2
14.7 Maritime transport in bulk accord	ding to IMO
instruments	Not applicable.
Transport/Additional information:	
ADR	
Limited quantities (LQ)	1L
Excepted quantities (EQ)	Code: E0
	Not permitted as Excepted Quantity
	Code: E0
	Not permitted as Excepted Quantity
Transport category	2
Tunnel restriction code	D
IMDG	
Limited quantities (LQ)	1L
Excepted quantities (\widetilde{EQ})	Code: E0
~	Not permitted as Excepted Quantity
	Code: E0
	Code: E0 Not permitted as Excepted Quantity

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture · Poisons Act
- · Regulated explosives precursors
- None of the ingredients is listed.
- · Regulated poisons
- None of the ingredients is listed.
- · Reportable explosives precursors
- 67-64-1 acetone
- · Reportable poisons
- None of the ingredients is listed.
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P3a FLAMMABLE AEROSOLS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t
- \cdot Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t

(Contd. on page 12)

Listed

GB

Page 12/12

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 04.04.2024

Version number 208 (replaces version 207)

Revision: 30.03.2022

Trade name: SIMPLY SPRAYS GLOSSY BLACK 500 ML

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

(Contd. of page 11)

GB

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

- H201 Explosive; mass explosion hazard.
- H220 Extremely flammable gas.
- H225 Highly flammable liquid and vapour.
- H226 Flammable liquid and vapour.
- H280 Contains gas under pressure; may explode if heated.
- H302 Harmful if swallowed.
- H315 Causes skin irritation.
- H318 Causes serious eye damage.
- H319 Causes serious eye irritation.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.
- EUH066 Repeated exposure may cause skin dryness or cracking.
- Classification according to Regulation (EC) No 1272/2008

Data is based on internal technical data and technical data from suppliers.

· Department issuing SDS: R&D legislation and regulatory advisor

- · Contact: e-mail: sds-nl@european-aerosols.com
- Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail) ICAO: International Civil Aviation Organisation ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) VOC: Volatile Organic Compounds (USA, EU) DNEL: Derived No-Effect Level (UK REACH) PNEC: Predicted No-Effect Concentration (UK REACH) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Expl. 1.1: Explosives – Division 1.1 Flam. Gas 1A: Flammable gases - Category 1A Aerosol 1: Aerosols - Category 1 Press. Gas (Comp.): Gases under pressure - Compressed gas Flam. Liq. 2: Flammable liquids - Category 2 Flam. Liq. 3: Flammable liquids – Category 3 Acute Tox. 4: Acute toxicity - Category 4 Skin Irrit. 2: Skin corrosion/irritation – Category 2 Eye Dam. 1: Serious eye damage/eye irritation - Category 1 Eye Irrit. 2: Serious eye damage/eye irritation – Category 2 STOT SE 3: Specific target organ toxicity (single exposure) - Category 3 • * Data compared to the previous version altered.