

Page 1/12

# Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 04.04.2024 Version number 114 (replaces version 113) Revision: 30.03.2022

#### SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: SIMPLY SPRAYS CLEAR LACQUER 500 ML
- · Article number: SP023
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

· Sector of Use

SU21 Consumer uses: Private households / general public / consumers

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

- · Product category Paint remover
- · Process category

PROC7 Industrial spraying

PROC11 Non industrial spraying

- · Application of the substance / the mixture Paint
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

European Aerosols B.V.\*

Wolfraamweg 2

NL-8471 XC Wolvega

The Netherlands

Tel: +31 (0)561 694400

e-mail: sds-nl@european-aerosols.com

- \*Formerly known as Motip Dupli B.V.
- · Further information obtainable from: Department Product Safety
- 1.4 Emergency telephone number: +31 (0)561-694400 (09:00h - 17:00h)

UK: NPIS National Poisons Information Centre Tel: +44 0344 892 0111

#### SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.



Eye Dam. 1 H318 Causes serious eye damage.



Skin Irrit. 2 H315 Causes skin irritation.

STOT SE 3 H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness.

(Contd. on page 2)

Printing date 04.04.2024 Version number 114 (replaces version 113) Revision: 30.03.2022

Trade name: SIMPLY SPRAYS CLEAR LACQUER 500 ML

(Contd. of page 1)

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

· Hazard pictograms







GHS02

GHS05

- · Signal word Danger
- · Hazard-determining components of labelling:

butan-1-ol

Hydrocarbons, C9, aromatics

xylene

*Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane* 

· Hazard statements

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

H315 Causes skin irritation.

Causes serious eye damage. H318

H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness.

Harmful to aquatic life with long lasting effects. H412

· Precautionary statements

If medical advice is needed, have product container or label at hand. P101

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211 Do not spray on an open flame or other ignition source.

Do not pierce or burn, even after use. P251

P260 Do not breathe spray.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of contents / container in accordance with regional regulations.

Additional information:

Buildup of explosive mixtures possible without sufficient ventilation.

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.

#### SECTION 3: Composition/information on ingredients

- · 3.2 Mixtures
- · **Description:** Mixture of substances listed below with nonhazardous additions.
- · Dangerous components:

CAS: 115-10-6 EINECS: 204-065-8 Index number: 603-019-00-8 Reg.nr.: 01-2119472128-37

dimethyl ether

🚯 Flam. Gas 1A, H220 Press. Gas (Comp.), H280

(Contd. on page 3)

50-<75%

Printing date 04.04.2024 Version number 114 (replaces version 113) Revision: 30.03.2022

Trade name: SIMPLY SPRAYS CLEAR LACQUER 500 ML

F.G. 1 010 ((0.5		Contd. of page
EC number: 918-668-5 Reg.nr.: 01-2119455851-35	Hydrocarbons, C9, aromatics  Flam. Liq. 3, H226  Asp. Tox. 1, H304  Aquatic Chronic 2, H411  STOT SE 3, H335-H336  EUH066	10-<12.5
EC number: 921-024-6 Reg.nr.: 01-2119475514-35	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane  Flam. Liq. 2, H225 Asp. Tox. 1, H304 Aquatic Chronic 2, H411 Skin Irrit. 2, H315; STOT SE 3, H336	5-<10%
EC number: 905-588-0 Reg.nr.: 01-2119488216-32-xxxx	xylene Flam. Liq. 3, H226 STOT RE 2, H373; Asp. Tox. 1, H304 Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	5-<10%
CAS: 71-36-3 EINECS: 200-751-6 Index number: 603-004-00-6 Reg.nr.: 01-2119484630-38	butan-1-ol Flam. Liq. 3, H226 Eye Dam. 1, H318 Acute Tox. 4, H302; Skin Irrit. 2, H315; STOT SE 3, H335-H336	5-<10%
CAS: 100-41-4 EINECS: 202-849-4 Index number: 601-023-00-4 Reg.nr.: 01-2119489370-35	ethylbenzene  Flam. Liq. 2, H225  STOT RE 2, H373; Asp. Tox. 1, H304  Acute Tox. 4, H332  Aquatic Chronic 3, H412	<2.5%

#### Additional information:

The content of Benzene (EINECS-Nr. 200-753-7) in the ingredients is less than 0,1% (Note P Annex 1A 1272/2008 EU), so the classification as carcinogen need not to apply. For the wording of the listed hazard phrases refer to section 16.

#### SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

Rinse opened eye for several minutes under running water. Then consult a doctor.

- · After swallowing: Drink plenty of water and provide fresh air. Call for a doctor immediately.
- · 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- 4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

### SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents: Use fire extinguishing methods suitable to surrounding conditions.
- 5.2 Special hazards arising from the substance or mixture

  During heating or in case of fire poisonous gases are produced.
- · 5.3 Advice for firefighters -
- · Protective equipment: Mouth respiratory protective device.

GB

Printing date 04.04.2024 Version number 114 (replaces version 113) Revision: 30.03.2022

Trade name: SIMPLY SPRAYS CLEAR LACQUER 500 ML

(Contd. of page 3)

#### SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Mount respiratory protective device.

Wear protective equipment. Keep unprotected persons away.

Keep away from ignition sources.

· 6.2 Environmental precautions:

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/surface or ground water.

· 6.3 Methods and material for containment and cleaning up:

Use neutralising agent.

Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation.

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

#### SECTION 7: Handling and storage

- · 7.1 Precautions for safe handling Ensure good ventilation/exhaustion at the workplace.
- · Information about fire and explosion protection:

Do not spray onto a naked flame or any incandescent material.

Keep ignition sources away - Do not smoke.

Keep respiratory protective device available.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles:

Observe official regulations on storing packagings with pressurised containers.

- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep container tightly sealed.
- · Storage class: 2 B
- · 7.3 Specific end use(s) No further relevant information available.

#### SECTION 8: Exposure controls/personal protection

- · 8.1 Control parameters
- · Ingredients with limit values that require monitoring at the workplace:

#### 115-10-6 dimethyl ether

WEL Short-term value: 958 mg/m³, 500 ppm Long-term value: 766 mg/m³, 400 ppm

xylene

WEL Short-term value: 441 mg/m³, 100 ppm Long-term value: 220 mg/m³, 50 ppm Sk; BMGV

71-36-3 butan-1-ol

WEL | Short-term value: 154 mg/m³, 50 ppm | Sk

100-41-4 ethylbenzene

WEL Short-term value: 552 mg/m³, 125 ppm Long-term value: 441 mg/m³, 100 ppm

Sk

(Contd. on page 5)

Printing date 04.04.2024 Version number 114 (replaces version 113) Revision: 30.03.2022

Trade name: SIMPLY SPRAYS CLEAR LACQUER 500 ML

DNELs	(Contd. o	от ра
	ons, C9, aromatics	
Oral	DNEL 11 mg/kg /per day (Consumer, longterm systemic)	
Dermal	DNEL 25 mg/kg /per day (Worker, longterm systemic)	
	DNEL 11 mg/kg /per day (Consumer, longterm systemic)	
Inhalative	DNEL 150 mg/m3 (Worker, longterm systemic)	
	DNEL 32 mg/m3 (Consumer, longterm systemic)	
Hydrocarb	ons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane	
Oral	DNEL   699 mg/kg (Consumer, longterm systemic)	
Dermal	DNEL 773 mg/kg (Worker, longterm systemic)	
	DNEL 699 mg/kg (Consumer, longterm systemic)	
Inhalative	DNEL 2035 mg/m3 (Worker, longterm systemic)	
	DNEL 608 mg/m3 (Consumer, longterm systemic)	
xylene		
Oral	DNEL 1.6 mg/kg /per day (Consumer, longterm systemic)	
Dermal	DNEL 180 mg/kg /per day (Worker, longterm systemic)	
Inhalative	DNEL 211 mg/m3 (Worker, longterm systemic)	
	DNEL 221 mg/m3 (Worker, longterm local)	
	DNEL 442 mg/m3 (Worker, acute systemic)	
	DNEL 289 mg/m3 (Worker, acute local)	
	DNEL 14.8 mg/m3 (Consumer, longterm systemic)	
	DNEL 260 mg/m3 (Consumer; acute systemic)	
	DNEL 65.3 mg/m3 (Consumer, longterm local)	
	DNEL 260 mg/m3 (Consumer, acute local)	
71-36-3 bu	tan-1-ol	
Oral	DNEL 3.125 mg/kg /per day (Consumer, longterm systemic)	
Inhalative	DNEL 310 mg/m3 (Worker, longterm local)	
	DNEL 55 mg/m3 (Consumer, longterm local)	
PNECs		
71-36-3 bu	tan-1-ol	
PNEC 0.0	82 mg/l (Freshwater)	
PNEC 0.0	082 mg/l (Seawater)	
PNEC 2.2	5 mg/l (Sporadic release)	
PNEC 247	76 mg/l (Sewage treatment plant)	
	78 mg/kg (Freshwater sediment)	
	178 mg/kg (Seawater sediment)	
	15 mg/kg (Soil)	
	s with biological limit values:	
xylene		
-	0 mmol/mol creatinine	
	edium: urine	
	mpling time: post shift	
Pa	rameter: methyl hippuric acid	

- · 8.2 Exposure controls
- · Appropriate engineering controls No further data; see section 7.

(Contd. on page 6)

Printing date 04.04.2024 Version number 114 (replaces version 113) Revision: 30.03.2022

Trade name: SIMPLY SPRAYS CLEAR LACQUER 500 ML

(Contd. of page 5)

#### · Individual protection measures, such as personal protective equipment

#### · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Avoid contact with the skin.

Avoid contact with the eyes and skin.

Avoid contact with the eyes.

· Respiratory protection:



In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Filter A2/P3

· Hand protection



Protective gloves

#### · Material of gloves

Butyl rubber, BR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

#### · Penetration time of glove material

Butyl rubber gloves with a thickness of 0.4 mm are resistant to:

Acetone: 480 min Butyl acetate: 60 min Ethyl acetate: 170 min Xylene: 42 min

Butyl rubber gloves with a thickness of 0.4 mm are solvent resistant for 42-480 minutes. As protective measure, we recommend that users and responsible persons for work safety assume solvent resistance length of 42 minutes. Considering the data in section 3 of this SDS, one can assume longer resistance length in particular cases.

· Eye/face protection



Tightly sealed goggles

#### SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

Physical state
Colour:
Odour:
Odour threshold:
Melting point/freezing point:

Aerosol
Colourless
Solvent-like
Not determined.
Undetermined.

· Boiling point or initial boiling point and boiling

range Not applicable, as aerosol.

· Flammability Not applicable.

· Lower and upper explosion limit

• Lower: 0.7 Vol % (Hydrocarbons, C9, aromatics)
• Upper: 26.2 Vol % (115-10-6 dimethyl ether)

(Contd. on page 7)

Printing date 04.04.2024 Version number 114 (replaces version 113) Revision: 30.03.2022

Trade name: SIMPLY SPRAYS CLEAR LACQUER 500 ML

(Contd. of page 6)

· Flash point: Not applicable, as aerosol.

>200 °C (>392 °F) (Hydrocarbons, C6-C7, n-alkanes, · Auto-ignition temperature:

isoalkanes, cyclics, <5% n-hexane)

· Decomposition temperature: Not determined. Not determined  $\cdot pH$ 

· Viscosity:

· Kinematic viscosity Not determined. · Dynamic: Not determined.

·Solubility

· water: Not miscible or difficult to mix.

· Partition coefficient n-octanol/water (log value) Not determined.

· Vapour pressure at 20 °C (68 °F): 4000 hPa (3000.2 mm Hg)

Density and/or relative density

Density at 20 °C (68 °F): 0.8 g/cm3 (6.7 lbs/gal) · Relative density Not determined. · Vapour density Not determined.

· 9.2 Other information

· Appearance:

· Form: Aerosol

· Important information on protection of health and environment, and on safety.

Not determined. · Explosive properties:

· Solvent content:

88.1 % · Organic solvents: · **VOC** (**EC**) 661.9 g/l · VOC-EU% 88.14 % 11.7% · Solids content:

· Change in condition

Not applicable. · Evaporation rate

· Information with regard to physical hazard classes

Void · Explosives Void · Flammable gases

Extremely flammable aerosol. Pressurised container: · Aerosols

May burst if heated.

· Oxidising gases Void · Gases under pressure Void · Flammable liquids Void · Flammable solids Void · Self-reactive substances and mixtures Void Pyrophoric liquids Void · Pyrophoric solids Void · Self-heating substances and mixtures Void · Substances and mixtures, which emit flammable gases in contact with water Void · Oxidising liquids Void

· Oxidising solids Void · Organic peroxides Void · Corrosive to metals Void · Desensitised explosives Void

#### SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

Printing date 04.04.2024 Version number 114 (replaces version 113) Revision: 30.03.2022

Trade name: SIMPLY SPRAYS CLEAR LACQUER 500 ML

(Contd. of page 7)

- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

#### SECTION 11: Toxicological information

- · 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Acute toxicity Based on available data, the classification criteria are not met.

Tichic loxi	ony Buseu o	n uvaluate data, the classification of the hat met.
· <i>LD/LC50</i> 1	values relev	ant for classification:
Hydrocarb	ons, C9, ar	omatics
Oral	LD50	>5000 mg/kg (rat) (OECD 401)
Dermal	LD50	>2000 mg/kg (rab) (OECD 402)
Hydrocarb	ons, C6-C7	, n-alkanes, isoalkanes, cyclics, <5% n-hexane
Oral	LD50	>5840 mg/kg (rat)
Dermal	LD50	>2920 mg/kg (rab)
Inhalative	LC50 / 4h	>25.2 mg/l (rat)
xylene		
Oral	LD50	3523 mg/kg (rat)
Dermal	LD50	2000 mg/kg (rabbit)
Inhalative	LC50 / 4 h	29000 mg/m3 (rat)
71-36-3 bu	tan-1-ol	
Oral	LD50	2292 mg/kg (rat)
Dermal	LD50	3430 mg/kg (rabbit)
Inhalative	LC50 / 4 h	17000 mg/m3 (rat)
100-41-4 e	thylbenzene	?
Oral	LD50	3500 mg/kg (rat)

- · Skin corrosion/irritation Causes skin irritation.
- · Serious eye damage/irritation Causes serious eye damage.
- · Respiratory or skin sensitisation No sensitising effects known.
- STOT-single exposure May cause respiratory irritation. May cause drowsiness or dizziness.
- · 11.2 Information on other hazards
- · Endocrine disrupting properties

None of the ingredients is listed.

#### SECTION 12: Ecological information

· 12.1 Toxicity

Aquatic toxi	icity:
115-10-6 dii	nethyl ether
EC50 / 96 h	155 mg/l (algae)
LC50 / 48 h	>4000 mg/l (daphnia magna)
LC50/96 h	>4000 mg/l (fish)
Hydrocarbo	ns, C9, aromatics
EC50 / 48 h	302 mg/l (daphnia magna)
EC50 / 72 h	2.75 mg/l (Pseudokirchneriella subcapitata)
EC50 / 96 h	9.2 mg/l (Regenbogenforelle)
	(Contd. on no

(Contd. on page 9)

Printing date 04.04.2024 Version number 114 (replaces version 113) Revision: 30.03.2022

Trade name: SIMPLY SPRAYS CLEAR LACQUER 500 ML

(Contd. of page 8) Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane EC50 / 48 h 3 mg/l (daphnia magna) EC50 / 72 h | 30-100 mg/l (algae) LC50 / 96 h 11.4 mg/l (fish) xylene EC50 / 48 h 7.4 mg/l (daphnia magna) LC50 / 96 h | 13.5 mg/l (fish) 71-36-3 butan-1-ol LC50 / 96 h 1376 mg/l (fish)

- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · 12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

- · 12.7 Other adverse effects
- · Remark: Harmful to fish
- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Must not reach sewage water or drainage ditch undiluted or unneutralised.

Danger to drinking water if even small quantities leak into the ground.

Harmful to aquatic organisms

#### SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- · Recommendation:

Disposal must be made according to official regulations.

Disposal must be made according to official regulations.

141100 1		
· 14.1 UN number or ID number · ADR, IMDG, IATA	UN1950	
14.2 UN proper shipping name		
ADR	1950 AEROSOLS	
· IMDG	AEROSOLS	
· IATA	AEROSOLS, flammable	

Printing date 04.04.2024 Version number 114 (replaces version 113) Revision: 30.03.2022

Trade name: SIMPLY SPRAYS CLEAR LACQUER 500 ML

(Contd. of page 9) · 14.3 Transport hazard class(es)  $\cdot ADR$ · Class 2 5F Gases. ·Label 2.1 · IMDG, IATA 2.1 Gases. · Class ·Label 2.1 · 14.4 Packing group · ADR, IMDG, IATA not regulated · 14.5 Environmental hazards: Not applicable. · 14.6 Special precautions for user Warning: Gases. · Hazard identification number (Kemler code): · EMS Number: F-D,S-USW1 Protected from sources of heat. · Stowage Code SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters. SG69 For AEROSOLS with a maximum capacity of 1 · Segregation Code Segregation as for class 9. Stow "separated from" class 1 except for division 1.4. For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2. · 14.7 Maritime transport in bulk according to IMO Not applicable. instruments · Transport/Additional information: · Limited quantities (LQ) Code: E0 · Excepted quantities (EQ) Not permitted as Excepted Quantity Code: E0 Not permitted as Excepted Quantity · Transport category · Tunnel restriction code D· Limited quantities (LQ) 1L· Excepted quantities (EQ) Code: E0 Not permitted as Excepted Quantity Code: E0 Not permitted as Excepted Quantity

(Contd. on page 11)

Printing date 04.04.2024 Version number 114 (replaces version 113) Revision: 30.03.2022

Trade name: SIMPLY SPRAYS CLEAR LACQUER 500 ML

(Contd. of page 10)

· UN "Model Regulation":

UN 1950 AEROSOLS, 2.1

#### SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Poisons Act
- · Regulated explosives precursors

None of the ingredients is listed.

· Regulated poisons

None of the ingredients is listed.

· Reportable explosives precursors

67-64-1 acetone

Listed

· Reportable poisons

None of the ingredients is listed.

- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P3a FLAMMABLE AEROSOLS
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

#### SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Relevant phrases
- H220 Extremely flammable gas.
- H225 Highly flammable liquid and vapour.
- H226 Flammable liquid and vapour.
- H280 Contains gas under pressure; may explode if heated.
- H302 Harmful if swallowed.
- H304 May be fatal if swallowed and enters airways.
- H312 Harmful in contact with skin.
- H315 Causes skin irritation.
- H318 Causes serious eye damage.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.
- H373 May cause damage to organs through prolonged or repeated exposure.
- H411 Toxic to aquatic life with long lasting effects.
- H412 Harmful to aquatic life with long lasting effects.

EUH066 Repeated exposure may cause skin dryness or cracking.

· Classification according to Regulation (EC) No 1272/2008

Data is based on internal technical data and technical data from suppliers.

- · Department issuing SDS: R&D legislation and regulatory advisor
- · Contact: e-mail: sds-nl@european-aerosols.com
- · Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

(Contd. on page 12)

Version number 114 (replaces version 113) Revision: 30.03.2022 Printing date 04.04.2024

Trade name: SIMPLY SPRAYS CLEAR LACQUER 500 ML

(Contd. of page 11)

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU) DNEL: Derived No-Effect Level (UK REACH)

PNEC: Predicted No-Effect Concentration (UK REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Flam. Gas 1A: Flammable gases - Category 1A

Aerosol 1: Aerosols - Category 1

Press. Gas (Comp.): Gases under pressure – Compressed gas

Flam. Liq. 2: Flammable liquids - Category 2 Flam. Liq. 3: Flammable liquids - Category 3

Acute Tox. 4: Acute toxicity – Category 4 Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation - Category 1

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2 Asp. Tox. 1: Aspiration hazard – Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2 Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3

\* \* Data compared to the previous version altered.