



EXPERIENCE TO PERFORM

TECHNICAL DATA SHEET

SVITOL EASY SILIKON

- DESCRIPTION OF THE PRODUCT

Lubricant and waterproof spray, also suited for plastic and rubber parts.

Easy Silikon spray enables the immediate creation of an oily protective film with no drips, thanks to the use of high volatility solvents.

Easy Silikon spray lubricates, protects and waterproofs.

Resists being washed away and rubbing. It works in a wide temperature range

(-40 to +260°C). Prevents ageing of seals, rubber, plastic and imitation leather parts. Prevents metals oxidation. Protects locks and other mechanisms from frost. Protects electric systems from damp and corrosion.

Waterproofs the materials it comes into contact with, such as boots, bags etc.

- FIELDS OF USE

Ideal for handmade articles and equipment with many parts in plastic and rubber that are exposed to humidity. As it is transparent and colourless, it is particularly suitable for precision equipment.

Also ideal as mould release agent.

- TECHNICAL FEATURES

- | | |
|------------------------------|------------|
| ● Appearance | liquid |
| ● Colour | colourless |
| ● Odour | typical |
| ● Density at 15°C ASTM D1298 | 0.700 g/ml |
| ● Distillation range | 40 – 80°C |
| ● Viscosity (oil) | 12500 cSt |

- INSTRUCTIONS

Shake the can well before use. Spray from a distance of about 30-40 cm. For a more targeted and precise application, insert the straw into the special nozzle. If water-proofing a large area, create a thin and even film and do not use the straw.

- CAUTIONS

Test compatibility with the material to be treated before starting. Do not apply on live appliances, switch on only after the solvent has evaporated completely. Do not apply to hot surfaces.

- STORAGE

In unopened package at ambient temperature, at least 3 years.

- PACKAGE

Spray can
200mL
Code 2392
IT/EN/FR/ES/PT/DE/PL/NL/HU/LT/LV/ET/EL/RU/R
O

- NOTES

See the Safety Data Sheet for more information on product safety.

T.S. 01.07.2021

The data contained herein are the result of technological research by our laboratories and are given for informative purposes only. We exclude any liability deriving from the incorrect choice or application of the product and from the lack of the necessary precautions, which should be carefully checked by the user. For information, please contact our Technical Dept. on no. +39 02924361

AREXONS S.p.A. A SOCIO UNICO
Via Antica di Cassano, 23
20063 Cernusco sul Naviglio (MI) Italy
Capitale Sociale: €15.000.000,00 I.V.
Registro delle Imprese di Milano n. 09728360968
Codice Fiscale e Partita IVA 09728360968
Direzione e coordinamento ex art. 2497 c.c. PLI (Netherlands) B.V.
Centralino 02 92436.1
Fax 02 92436.306
www.arexons.com

A wholly-owned subsidiary of PETRONAS

Sistemi di gestione di qualità della società Arexons S.p.A.
certificati ISO 9001 da LRQA.

Sistemi di gestione di ambiente e sicurezza della società Arexons S.p.A.
certificati ISO 14001 e OHSAS 18001 da Bureau Veritas.

